

MATERIAL SAFETY DATA SHEET

**EPOXY TECHNOLOGY
14 FORTUNE DRIVE
BILLERICA, MA 01821**

PRODUCT NAME: EPO-TEK 301-2, Part A

EMERGENCY PHONE:
US/CANADA: 800-255-3924
INT'L COLLECT: + 813-248-0585

***HMIS: HEALTH- 2 FIRE-1 REACTIVITY- 0**

Carcinogen: NTP (No) IARC (No) OSHA (No)

DATE REVISED: 12/5/2008
REV: G

* HMIS CODE ratings are estimated by Epoxy Technology.

I. IDENTIFICATION & PHYSICAL DATA

PERCENT VOLATILE: NA
BOILING POINT: NA
VAPOR DENSITY: >Air
APPEARANCE: colorless to yellow liquid
ODOR: Mild

VAPOR PRESSURE: NA
SOLUBILITY IN WATER: None
EVAPORATION RATE: <BUAC
SPECIFIC GRAVITY: 1.02

II. HAZARDOUS INGREDIENTS

CAS#

WT%

Diglycidyl Ether of Bisphenol A

1675-54-3

75-100%

III. FIRE & EXPLOSION DATA

FLASH POINT: > 485F
EXTINGUISHING MEDIA: Dry chemical, foam, carbon dioxide.
UNUSUAL FIRE & EXPLOSION HAZARDS: Avoid fumes liberated by heat.
SPECIAL FIRE FIGHTING PROCEDURES: Wear self contained breathing apparatus and complete personal protective equipment. Remove all ignition sources. Use a water spray to cool fire exposed containers.

IV. REACTIVITY DATA

STABILITY: Stable @ ambient temperatures
CONDITIONS TO AVOID: Excessive heat.
MATERIALS TO AVOID: Acids, bases, amines, and oxide materials
HAZARDOUS DECOMPOSITION PRODUCTS: Fumes produced when heated to decomposition may include carbon monoxide, and carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to be to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guarantee or representation is made as to the correctness or sufficiency of the information. The user of this product, either alone or in the combination with other products, and determine its environment regulatory compliance obligations under applicable federal or state laws.

EFFECTS OF OVEREXPOSURE

- INGESTION:** Toxicity is considered to be extremely low.
- INHALATION:** Vapors are unlikely due to physical properties.
- SKIN CONTACT:** Can cause dermatitis.
- EYE CONTACT:** Irritating to the eyes. Can cause injury.
- CHRONIC EFFECTS OF OVEREXPOSURE:** May cause temporary eye irritation .

EMERGENCY & FIRST AID PROCEDURES

- EYE CONTACT:** In case of eye contact, flush well with water. Get medical attention immediately.
- SKIN CONTACT:** In case of skin contact, clean with soap and water. Do not use solvents. Remove contaminated clothing.
- INGESTION:** Get medical attention immediately.
- INHALATION:** Remove employee to fresh air. If discomfort persists, get medical attention.

VI. SPILL OR LEAK PROCEDURES

- STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED:** Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Absorb spillage with inert material and dispose.
- WASTE DISPOSAL METHOD:** Incinerate or use hazardous waste treatment procedures that are in accordance with federal, state and local regulations.

VII. SPECIAL PROTECTION INFORMATION

- RESPIRATORY PROTECTION:** Wear an approved respirator whenever high level exposure to vapors or mist is anticipated.
- VENTILATION:** Local exhaust recommended for exposure control.
- PROTECTIVE GLOVES:** Impervious gloves - neoprene or equivalent. A combination of barrier cream and gloves is recommended.
- EYE PROTECTION:** Chemical splash goggles recommended.
- OTHER PROTECTIVE EQUIPMENT:** For operations where contact can occur, use a face shield and impervious apron. A safety shower and eye wash facility should be available.

VIII. SPECIAL PRECAUTIONS: Avoid contact with skin and eyes. Avoid breathing vapors. Keep containers closed when not in use. Remove all contaminated clothing immediately and wash. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential - protective skin oils can be dissolved by solvents.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: EPO-TEK 301-2, Part B

***HMIS: HEALTH- 3 FIRE-1 REACTIVITY-0**

Carcinogen: NTP (No) IARC (No) OSHA (No)

* HMIS CODE ratings are estimated by Epoxy Technology.

EPOXY TECHNOLOGY

**14 FORTUNE DRIVE
BILLERICA, MA 01821**

EMERGENCY PHONE:

US/CANADA: 800-255-3924

INT'L COLLECT: + 813-248-0585

DATE REVISED: 12/5/2008

REV: G

I. IDENTIFICATION & PHYSICAL DATA

PERCENT VOLATILE: NA
BOILING POINT: 500°F
VAPOR DENSITY: >Air
APPEARANCE: Clear liquid
ODOR: Mild

VAPOR PRESSURE: 1 @ 100C
SOLUBILITY IN WATER: NA
EVAPORATION RATE: <BUAC
SPECIFIC GRAVITY: 0.95

II. HAZARDOUS INGREDIENTS

	CAS#	WT%
Polyoxypropylenediamine	9046-10-0	75-100%

III. FIRE & EXPLOSION DATA

FLASH POINT: >250F

EXTINGUISHING MEDIA: Dry chemical, foam, carbon dioxide.

UNUSUAL FIRE & EXPLOSION HAZARDS: Avoid fumes liberated by heat.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self contained breathing apparatus and complete personal protective equipment. Remove all ignition sources. Use a water spray to cool fire exposed containers.

IV. REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Excessive heat.

MATERIALS TO AVOID: Strong oxidizing and reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Fumes produced when heated to decomposition may include oxides of nitrogen, carbon monoxide, and carbon dioxide.

The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guarantee or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine its environmental regulatory compliance obligations under any applicable under any applicable federal or state laws.

V. HEALTH HAZARD DATA

EPO-TEK 301-2, Part B

EFFECTS OF OVEREXPOSURE

INGESTION: Contains materials that may be moderately toxic. Ingestion can severely upset the gastric system.

INHALATION: Hot vapors can cause headaches, nausea, dizziness, and respiratory irritation, if inhaled.

SKIN CONTACT: Corrosive; expected to cause severe skin damage with burns and blistering.

EYE CONTACT: Extremely irritating with possible permanent eye injury.

CHRONIC EFFECTS OF OVEREXPOSURE: Combinations of above conditions can be experienced.

EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT: In case of eye contact, flush well with water. Get medical attention immediately.

SKIN CONTACT: In case of skin contact, clean with soap and water. Do not use solvents. Remove contaminated clothing.

INGESTION: Give large quantities of water. Get medical attention immediately.

INHALATION: Can be irritating to respiratory track. Remove to fresh air. Get medical attention if discomfort persists.

VI. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED: Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Absorb spillage with inert material and dispose.

WASTE DISPOSAL METHOD: Incinerate or use hazardous waste treatment procedures that are in accordance with federal, state and local regulations.

VII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear an approved respirator whenever high level exposure to vapors or mist is anticipated.

VENTILATION: Local exhaust recommended for exposure control.

PROTECTIVE GLOVES: Impervious gloves - neoprene or equivalent. A combination of barrier cream and gloves is recommended.

EYE PROTECTION: Chemical splash goggles must be worn.

OTHER PROTECTIVE EQUIPMENT: For operations where contact can occur, use a face shield and impervious apron. A safety shower and eye wash facility should be available.

VIII. SPECIAL PRECAUTIONS: Avoid contact with skin and eyes. Avoid breathing vapors. Keep containers closed when not in use. Remove all contaminated clothing immediately and wash. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential - protective skin oils can be dissolved by solvents.

REGULATORY INFORMATION

EPOXY TECHNOLOGY
14 FORTUNE DRIVE
BILLERICA, MA 01821
TEL: (978) 667-3805

PRODUCT NAME: EPO-TEK 301-2
DATE REVISED: 12/5/2008
REV: G

1. SARA TITLE III SECTION 313 SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right To Know Act of 1986 (40 CFR 372): None

2. TSCA Inventory Status

All the components of this product are listed on the TSCA Inventory.

3. RCRA Status

This product contains the following chemicals listed on the 40 CFR Part 261.33: None

4. CERCLA Status

This product contains the following chemicals listed on the 40 CFR Part 302.4: None

5. Transportation

Part A

Not Restricted

Part B

Proper Shipping Name: Amines, Liquid, Corrosive, N.O.S. (Polyoxypropylenediamine)
Hazard Class: 8
Packing Group: III
ID Number: UN2735
Transport Label(s): Corrosive Liquid

The information contained herein is given in good faith. However, no guarantee or warranty of any kind expressed or implied is made with respect to this information.