

MATERIAL SAFETY DATA SHEET**PRODUCT NAME:** EPO-TEK 920, Part A***HMIS:** HEALTH- 2 FIRE-1 REACTIVITY- 0**Carcinogen:** NTP (No) IARC (No) OSHA (No)

* HMIS CODE ratings are estimated by Epoxy Technology.

EPOXY TECHNOLOGY**14 FORTUNE DRIVE
BILLERICA, MA 01821****EMERGENCY PHONE:**

US/CANADA: 800-255-3924

INT'L COLLECT: + 813-248-0585

DATE REVISED: 9/19/01**REV:** B

I. IDENTIFICATION & PHYSICAL DATA**PERCENT VOLATILE:** NA**BOILING POINT:** NA**VAPOR DENSITY:** >Air**APPEARANCE:** Opaque paste**ODOR:** Mild**VAPOR PRESSURE:** NA**SOLUBILITY IN WATER:** Low**EVAPORATION RATE:** <BUAC**SPECIFIC GRAVITY:** NA

II. HAZARDOUS INGREDIENTS**CAS#****WT %****TOXICITY DATA**

Reaction product of epichlorohydrin & bisphenol A 025085-99-8 5-10% See Ingredient Sheet 110104

Reaction product of epichlorohydrin and bisphenol A requires reporting under OSHA's Hazardous Communication Standards, 1910.1200.

III. FIRE & EXPLOSION DATA**FLASH POINT:** NA**EXTINGUISHING MEDIA:** Dry chemical, foam, carbon dioxide.**UNUSUAL FIRE & EXPLOSION HAZARDS:** Avoid fumes liberated by heat.**SPECIAL FIRE FIGHTING PROCEDURES:** Wear self contained breathing apparatus and complete personal protective equipment. Remove all ignition sources. Use a water spray to cool fire exposed containers.

IV. REACTIVITY DATA**STABILITY:** Stable**HAZARDOUS POLYMERIZATION:** Will not occur.**CONDITIONS TO AVOID:** Excessive heat.**MATERIALS TO AVOID:** Strong oxidizing and reducing agents.**HAZARDOUS DECOMPOSITION PRODUCTS:** Fumes produced when heated to decomposition may include carbon monoxide, and carbon dioxide.

The information and recommendations contained in this msds have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the msds was prepared. No warranty, guarantee, or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what measures are necessary to safely use this product, either alone or in the combination with other products, and to determine its environmental regulatory compliance obligations under applicable federal or state laws.

EFFECTS OF OVER EXPOSURE

INGESTION: No specific information available.

INHALATION: Hot vapors can cause headaches, nausea, dizziness, and respiratory irritation.

SKIN CONTACT: Can cause dermatitis.

EYE CONTACT: Irritating to the eyes. Can cause injury.

CHRONIC EFFECTS OF OVER EXPOSURE: Can cause dermatitis and sensitization.

EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT: In case of eye contact, flush with water for at least 15 minutes. Get medical attention immediately.

SKIN CONTACT: In case of skin contact, clean with soap and water. Do not use solvents. Remove contaminated clothing.

INGESTION: Get medical attention immediately.

INHALATION: Remove employee to fresh air. If discomfort persists, get medical attention.

VI. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED: Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Absorb spillage with inert material and dispose.

WASTE DISPOSAL METHOD: Incinerate or use hazardous waste treatment procedures that are in accordance with federal, state and local regulations.

VII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear an NIOSH approved respirator whenever high level exposure to vapors or mist is anticipated.

VENTILATION: Local exhaust recommended for exposure control.

PROTECTIVE GLOVES: Impervious gloves - neoprene or equivalent. A combination of barrier cream and gloves is recommended.

EYE PROTECTION: Chemical splash goggles recommended.

OTHER PROTECTIVE EQUIPMENT: For operations where contact can occur, use a face shield and impervious apron. A safety shower and eye wash facility should be available.

VIII. SPECIAL PRECAUTIONS: Avoid contact with skin and eyes. Avoid breathing vapors. Keep containers closed when not in use. Remove all contaminated clothing immediately and wash. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential - protective skin oils can be dissolved by solvents.

MATERIAL SAFETY DATA SHEET**PRODUCT NAME:** EPO-TEK 920, Part B***HMIS: HEALTH- 3 FIRE-1 REACTIVITY- 0****Carcinogen: NTP (No) IARC (No) OSHA (No)**

* HMIS CODE ratings are estimated by Epoxy Technology.

EPOXY TECHNOLOGY**14 FORTUNE DRIVE
BILLERICA, MA 01821****EMERGENCY PHONE:**

US/CANADA: 800-255-3924

INT'L COLLECT: + 813-248-0585

DATE REVISED: 9/19/01**REV: B**

I. IDENTIFICATION & PHYSICAL DATA**PERCENT VOLATILE:** NA**BOILING POINT:** NA**VAPOR DENSITY:** >Air**APPEARANCE:** Amber liquid**ODOR:** Mild**VAPOR PRESSURE:** NA**SOLUBILITY IN WATER:** NA**EVAPORATION RATE:** <BUAC**SPECIFIC GRAVITY:** 1.02

II. HAZARDOUS INGREDIENTS**CAS#****WT %****TOXICITY DATA**

Imidazole

288-32-4

25-50%

See Ingredient Sheet 210803.

Imidazole is the only hazardous ingredient that requires reporting per Sara Title III, under 311 and 312.

III. FIRE & EXPLOSION DATA**FLASH POINT:** >200F**EXTINGUISHING MEDIA:** Dry chemical, foam, carbon dioxide.**UNUSUAL FIRE & EXPLOSION HAZARDS:** Avoid fumes liberated by heat.**SPECIAL FIRE FIGHTING PROCEDURES:** Wear self contained breathing apparatus and complete personal protective equipment. Remove all ignition sources. Use a water spray to cool fire exposed containers.

IV. REACTIVITY DATA**STABILITY:** Stable**HAZARDOUS POLYMERIZATION:** Will not occur.**CONDITIONS TO AVOID:** Excessive heat.**MATERIALS TO AVOID:** Strong oxidizing and reducing agents.**HAZARDOUS DECOMPOSITION PRODUCTS:** Fumes produced when heated to decomposition may include oxides of nitrogen, carbon monoxide, and carbon dioxide.

The information and recommendation contained in this MSDS have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guarantee or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine its environmental regulatory compliance obligations under any applicable federal or state laws.

V. HEALTH HAZARD DATA

EPO-TEK 920, Part B

EFFECTS OF OVEREXPOSURE

INGESTION: Ingestion can severely upset the gastric system.

INHALATION: Hot vapors can cause headaches, nausea, dizziness, and respiratory irritation, if inhaled.

SKIN CONTACT: Mildly irritating in rabbit dermal irritation studies. May cause dermatitis and skin sensitization in some individuals.

EYE CONTACT: Causes eye burns in rabbit irritation studies. Irritating to the eyes. Can cause injury.

CHRONIC EFFECTS OF OVEREXPOSURE: Repeated and/or prolonged exposures may result in: adverse

Respiratory effects(such as cough, tightness of chest or shortness of breath), adverse eye effects (such as

Conjunctivitis corneal damage), adverse eye effects (such as rash, irritation or corrosion).

EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT: In case of eye contact, flush with water for at least 15 minutes. Get medical attention immediately.

SKIN CONTACT: In case of skin contact, clean with soap and water. Do not use solvents. Remove contaminated clothing.

INGESTION: Get medical attention immediately.

INHALATION: Remove employee to fresh air. If discomfort persists, get medical attention.

VI. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED: Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area.

Absorb spillage with inert material and dispose.

WASTE DISPOSAL METHOD: Incinerate or use hazardous waste treatment procedures that are in accordance with federal, state and local regulations.

VII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear an NIOSH approved respirator whenever high level exposure to vapors or mist is anticipated.

VENTILATION: Local exhaust recommended for exposure control.

PROTECTIVE GLOVES: Impervious gloves - neoprene or equivalent. A combination of barrier cream and gloves is recommended.

EYE PROTECTION: Chemical splash goggles recommended.

OTHER PROTECTIVE EQUIPMENT: For operations where contact can occur, use a face shield and impervious apron. A safety shower and eye wash facility should be available.

SPECIAL PRECAUTIONS: Avoid contact with skin and eyes. Avoid breathing vapors. Keep containers closed when not in use. Remove all contaminated clothing immediately and wash. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential - protective skin oils can be dissolved by solvents

REGULATORY INFORMATION

**EPOXY TECHNOLOGY
14 FORTUNE DRIVE
BILLERICA, MA 01821
TEL: (978) 667 – 3805**

PRODUCT NAME: EPO-TEK 920
DATE REVISED: 6/26/2006
REV: D

1. SARA TITLE III SECTION 313 SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right To Know Act of 1986 (40 CFR 372): None

2. TSCA Inventory Status

All the components of this product are listed on the TSCA Inventory.

3. RCRA Status

This product contains the following chemicals listed on the 40 CFR Part 261.33: None

4. CERCLA Status

This product contains the following chemicals listed on the 40 CFR Part 302.4: None

5. Transportation

Part A

Not Restricted

Part B

Proper Shipping Name: Corrosive, Liquid, Basic, Organic, N.O.S (Imidazole)
Hazard Class: 8
Packing Group: III
ID Number: UN3267
Transport Label(s): Corrosive Liquid

The information contained herein is given in good faith. However, no guarantee or warranty of any kind expressed or implied is made with respect to this information.

INGREDIENT SHEET**EPOXY TECHNOLOGY
14 FORTUNE DRIVE
BILLERICA, MA 01821****INGREDIENT CODE NUMBER:** 110104**EMERGENCY PHONE:**
US/CANADA: 800-255-3924
INT'L COLLECT: + 813-248-0585***HMIS: HEALTH (1) FLAMMIBILITY (1)
REACTIVITY (0)****DATE REVISED:** 10/13/00
REV: A**CARCINOGEN: NTP (No) IARC (No) OSHA (No)**

*HMIS CODE rating are estimated by Epoxy Technology

I. IDENTIFICATION & PHYSICAL DATAColor: Colorless to slight Yellow
Physical State: Liquid
Vapor Pressure: NA
Boiling Point: NAOdor: Slight
Solubility in Water: None
Specific Gravity: 1.16

II. HAZARDOUS INGREDIENTS**WT%****CAS #**

Reaction production of epichlorohydrin and bisphenol A

100%

025085-99-8

TOXICITY DATASkin(LD50): in rabbits is 20,000mg/kg.
Ingestion(LD50): in rats is >5000mg/kg
Mutagenicity: Animal mutagenicity, studies were negative.

III. FIRE AND EXPLOSION DATA**FLASH POINT:** 485 F**EXTINGUISHING MEDIA:** Foam, CO2, dry chemical.**UNUSUAL FIRE AND EXPLOSION HAZARDS:** None Known**FIRE FIGHTING EQUIPMENT:** Wear positive pressure self-contained breathing apparatus and full protective equipment.

IV. REACTIVITY DATA**STABILITY:** Stable**CONDITIONS TO AVOID:** Avoid storage at high temperatures.**HAZARDOUS DECOMPOSITION PRODUCTS:** None Known.**HAZARDOUS POLYMERIZATION:** Will not occur

The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to represent current opinion on the subject when the msds was prepared. No warranty, guarantee or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, whether alone or in combination with other products, and determine its environmental regulatory compliance obligations under applicable federal or state laws.

V. **HEALTH HAZARD DATA**

110104

EFFECTS OF OVER EXPOSURE

None Established.

EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT: Flush eyes with plenty of water.

SKIN CONTACT: Wash off in flowing water or shower.

INGESTION: No adverse effects anticipated by this route of exposure incidental to proper industrial handling.

INHALATION: No adverse effects anticipated by this route of exposure.

VI. **SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED: Soak up in absorbent material such as sand, or polypropylene or polyethylene fiber products and collect in suitable containers. Residual resin may be removed using steam or hot soapy water.

WASTE DISPOSAL METHOD: Employ waste disposal procedures that are in accordance with federal, state and local regulations.

VII. **SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION: Wear an approved respirator whenever exposure to air born vapors are anticipated.

VENTILATION: Local exhaust recommended for exposure control.

PROTECTIVE GLOVES: Impervious gloves-neoprene or equivalent. A combination of barrier cream and gloves is recommended.

EYE PROTECTION: Chemical splash goggles recommended.

OTHER PROTECTIVE EQUIPMENT: For operations where contact can occur, use a face shield and impervious apron. A safety shower and eye wash facility should be available.

VIII. **SPECIAL PRECAUTIONS:** Avoid contact with skin and eyes. Avoid breathing vapors generated by heating. Keep containers closed when not in use. Remove all contaminated clothing and wash.

INGREDIENT SHEET**EPOXY TECHNOLOGY
14 FORTUNE DRIVE
BILLERICA, MA 01821****INGREDIENT CODE NUMBER:** 210803***HMIS: HEALTH- 3 FIRE-1 REACTIVITY- 1****EMERGENCY PHONE:**

US/CANADA: 800-255-3924

INT'L COLLECT: + 813-248-0585

Carcinogen: NTP (No) IARC (No) OSHA (No)**DATE ISSUED:** 12/29/99

* HMIS CODE ratings are estimated by Epoxy Technology.

I. IDENTIFICATION & PHYSICAL DATA**PERCENT VOLATILE:** NA
BOILING POINT: 256 C
VAPOR DENSITY: NA
APPEARANCE: Amber solid
ODOR: Mild**VAPOR PRESSURE:** NA
SOLUBILITY IN WATER: 2410 gm/l
EVAPORATION RATE: NA
SPECIFIC GRAVITY: 1.03
MELTING POINT: 89 C

II. HAZARDOUS INGREDIENTS**CAS#****WT %****TOXICITY DATA**

Imidazole

288-32-4

99

ACGIH (TWA) = Not Established
OSHA PEL (TWA) = Not Established
TLV = 2mg/m3 (Established by supplier)
Oral LD50 (Rat) = 965 mg/kg
Eyes & Skin (Rabbit) = Severely
irritating, Corrosive.

Imidazole does not appear in Mass RTK hazardous substance list

III. FIRE & EXPLOSION DATA**FLASH POINT:** >200F**EXTINGUISHING MEDIA:** Dry chemical, foam, carbon dioxide, water fog.**UNUSUAL FIRE & EXPLOSION HAZARDS:** Avoid fumes liberated by heat.**SPECIAL FIRE FIGHTING PROCEDURES:** Wear self contained breathing apparatus and complete personal protective equipment. Remove all ignition sources. Use a water spray to cool fire exposed containers.

IV. REACTIVITY DATA**STABILITY:** Stable**HAZARDOUS POLYMERIZATION:** Will not occur.**CONDITIONS TO AVOID:** Excessive heat.**MATERIALS TO AVOID:** Acids**HAZARDOUS DECOMPOSITION PRODUCTS:** Fumes produced when heated to decomposition may include carbon monoxide, carbon dioxide, HCN, and oxides of nitrogen.

To the best of our knowledge, the information contained herein is accurate. Epoxy Technology Inc., however, assumes no liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

EFFECTS OF OVEREXPOSURE

INGESTION: Ingestion causes severe gastric disturbances.

INHALATION: Can be severely irritating to the respiratory tract. This type of exposure is avoidable with adequate, local exhaust ventilation.

SKIN CONTACT: Skin contact with imidazole can result in severe irritation. This type of exposure is avoidable with local exhaust ventilation, adequate clothing, the use of barrier cream, gloves, and chemical splash goggles.

EYE CONTACT: Eye contact with imidazole can result in severe irritation. Swelling and corneal clouding may result. This type of exposure is avoidable with, local exhaust ventilation and the use of chemical splash goggles.

CHRONIC/ACUTE EFFECTS OF EXPOSURE: Specific information not available.

EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT: Wash eyes with running water for, at least, 15 minutes. Get immediate medical attention.

SKIN CONTACT: Wash affected areas with soap and water. Do not use solvents for cleaning. Remove contaminated clothing.

INGESTION: Do not induce vomiting. If conscious, dilute with water or milk. Get immediate medical attention.

INHALATION: Can be irritating to respiratory tract. Remove to fresh air. Get medical attention if discomfort persists.

VI. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED: Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Absorb spillage with inert material and dispose.

WASTE DISPOSAL METHOD: Incinerate or use hazardous waste treatment procedures that are in accordance with federal, state and local regulations.

VII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear an approved respirator whenever high level exposure to vapors or mist is anticipated.

VENTILATION: Local exhaust recommended for exposure control.

PROTECTIVE GLOVES: Impervious gloves - neoprene or equivalent. A combination of barrier cream and gloves is recommended.

EYE PROTECTION: Chemical splash goggles required.

OTHER PROTECTIVE EQUIPMENT: For operations where contact is possible, use chemical splash goggles, adequate clothing coverage, and gloves. A safety shower and eye wash facility must be located in reasonable proximity to work stations.

VIII. SPECIAL PRECAUTIONS: Avoid contact with skin and eyes. Avoid breathing vapors. Keep containers closed when not in use. Remove all contaminated clothing immediately and wash. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased absorption potential. Protective skin oils can be dissolved by solvents.