

MATERIAL SAFETY DATA SHEET

**EPOXY TECHNOLOGY
14 FORTUNE DRIVE
BILLERICA, MA 01821**

PRODUCT NAME: EPO-TEK EH100, Part A

EMERGENCY PHONE:
US/CANADA: 800-255-3924
INT'L COLLECT: + 813-248-0585

***HMIS: HEALTH-2 FIRE-1 REACTIVITY-0**

Carcinogen: NTP (No) IARC (No) OSHA (No)

DATE REVISED: 11/10/11
REV: D

* HMIS CODE ratings are estimated by Epoxy Technology.

I. IDENTIFICATION & PHYSICAL DATA

PERCENT VOLATILE: NA
BOILING POINT: NA
VAPOR DENSITY: >Air
APPEARANCE: Silver paste
ODOR: Mild

VAPOR PRESSURE: NA
SOLUBILITY IN WATER: Low
EVAPORATION RATE: <BUAC
SPECIFIC GRAVITY: NA

II. HAZARDOUS INGREDIENTS

CAS #

WT %

Silver Flake	7440-22-4	70-80%
Epoxy Phenol Novolac	28064-14-4	15-30%

Silver flake is the only ingredient that requires reporting according to Sara Title III, under section 313. Epoxy Phenol Novolac requires reporting according to OSHA Communication Standards under 29CFR.

III. FIRE & EXPLOSION DATA

FLASH POINT: >200 F
EXTINGUISHING MEDIA: Dry chemical, foam, carbon dioxide.
UNUSUAL FIRE & EXPLOSION HAZARDS: Avoid fumes liberated by heat.
SPECIAL FIRE FIGHTING PROCEDURES: Wear self contained breathing apparatus and complete personal protective equipment. Remove all ignition sources. Use a water spray to cool fire exposed containers.

IV. REACTIVITY DATA

STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur.
CONDITIONS TO AVOID: Excessive heat.
MATERIALS TO AVOID: Strong oxidizing and reducing agents.
HAZARDOUS DECOMPOSITION PRODUCTS: Fumes produced when heated to decomposition may include carbon monoxide, and carbon dioxide.

The information and recommendations contained in this MSDS have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guarantee, or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what measures are necessary to safely use this product, either alone or in the combination with other products, and to determine its environmental regulatory compliance under applicable federal or state laws.

V. HEALTH HAZARD DATA

EPO-TEK EH100, Part A

EFFECTS OF OVER EXPOSURE

INGESTION: May be moderately toxic

INHALATION: Hot vapors can cause headaches, nausea, dizziness, and respiratory irritation.

SKIN CONTACT: Can cause dermatitis, sensitization.

EYE CONTACT: Irritating to the eyes. Can cause injury.

CHRONIC EFFECTS OF OVER EXPOSURE: Can cause dermatitis and sensitization.

EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT: In case of eye contact, flush with water at least 15 min. Get medical attention immediately.

SKIN CONTACT: In case of skin contact, clean with soap and water. Do not use solvents. Remove contaminated clothing.

INGESTION: Get medical attention immediately.

INHALATION: Remove employee to fresh air. If discomfort persists, get medical attention.

VI. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED: Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Absorb spillage with inert material and dispose.

WASTE DISPOSAL METHOD: Incinerate or use hazardous waste treatment procedures that are in accordance with federal, state and local regulations.

VII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear an approved respirator whenever high level exposure to vapors or mist is anticipated.

VENTILATION: Local exhaust recommended for exposure control.

PROTECTIVE GLOVES: Impervious gloves - neoprene or equivalent. A combination of barrier cream and gloves is recommended.

EYE PROTECTION: Chemical splash goggles recommended.

OTHER PROTECTIVE EQUIPMENT: For operations where contact can occur, use a face shield and impervious apron. A safety shower and eye wash facility should be available.

VIII. SPECIAL PRECAUTIONS: Avoid contact with skin and eyes. Avoid breathing vapors. Keep containers closed when not in use. Remove all contaminated clothing immediately and wash. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential - protective skin oils can be dissolved by solvents.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: EPO-TEK EH100, Part B

***HMIS: HEALTH- 2 FIRE-1 REACTIVITY- 0**

Carcinogen: NTP (No) IARC (No) OSHA (No)

* HMIS CODE ratings are estimated by Epoxy Technology.

**EPOXY TECHNOLOGY
14 FORTUNE DRIVE
BILLERICA, MA 01821**

EMERGENCY PHONE:
US/CANADA: 800-255-3924
INT'L COLLECT: + 813-248-0585

DATE REVISED: 11/10/11
REV: D

I. IDENTIFICATION & PHYSICAL DATA

PERCENT VOLATILE: NA
BOILING POINT: NA
VAPOR DENSITY: >Air
APPEARANCE: Clear Liquid
ODOR: Mild

VAPOR PRESSURE: NA
SOLUBILITY IN WATER: Low
EVAPORATION RATE: <BUAC
SPECIFIC GRAVITY: NA

II. HAZARDOUS INGREDIENTS

CAS #

WT %

Polyoxypropylenediamine

9046-10-0

75 –100%

Polyoxypropylenediamine requires reporting according to OSHA's Hazardous Communication Standards, 1910.1200.

III. FIRE & EXPLOSION DATA

FLASH POINT: >200F

EXTINGUISHING MEDIA: Dry chemical, foam, carbon dioxide.

UNUSUAL FIRE & EXPLOSION HAZARDS: Avoid fumes liberated by heat.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self contained breathing apparatus and complete personal protective equipment. Remove all ignition sources. Use a water spray to cool fire exposed containers.

IV. REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Excessive heat.

MATERIALS TO AVOID: Strong oxidizing and reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Fumes produced when heated to decomposition may include carbon monoxide, carbon dioxide, and oxides of nitrogen.

The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to be reliable and to represent the most reasonable current opinion of the subject when the MSDS was prepared. No warranty, guarantee, or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what measures are necessary to safely use this product, either alone or in the combination with other products, and to determine its environmental the combination with other products, and to determine its environmental regulatory compliance obligations under applicable federal or state laws.

EFFECTS OF OVER EXPOSURE

INGESTION: Ingestion may result in severe gastric disturbances. Gastrointestinal damage may result.

INHALATION: Hot vapors can cause headaches, nausea, dizziness, and respiratory irritation.

SKIN CONTACT: Mildly irritating in rabbit dermal irritation studies. May cause dermatitis and skin sensitization in some individuals.

EYE CONTACT: Causes eye burns in rabbit irritation studies. Irritating to the eyes. Can cause injury.

CHRONIC EFFECTS OF OVER EXPOSURE: In a single dose, this product may be toxic by ingestion. Irritation of the mouth, pharynx, and esophagus can develop following ingestion.

EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT: In case of eye contact, flush with water for at least 15 minutes. Get medical attention immediately.

SKIN CONTACT: In case of skin contact, clean with soap and water. Do not use solvents. Remove contaminated clothing.

INGESTION: Get medical attention immediately.

INHALATION: Remove employee to fresh air. If discomfort persists, get medical attention.

VI. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED: Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Absorb spillage with inert material and dispose.

WASTE DISPOSAL METHOD: Incinerate or use hazardous waste treatment procedures that are in accordance with federal, state and local regulations.

VII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear an NIOSH approved respirator whenever high level exposure to vapors or mist is anticipated.

VENTILATION: Local exhaust recommended for exposure control.

PROTECTIVE GLOVES: Impervious gloves - neoprene or equivalent. A combination of barrier cream and gloves is recommended.

EYE PROTECTION: Chemical splash goggles recommended.

OTHER PROTECTIVE EQUIPMENT: For operations where contact can occur, use a face shield and impervious apron. A safety shower and eye wash facility should be available.

VIII. SPECIAL PRECAUTIONS: Avoid contact with skin and eyes. Avoid breathing vapors. Keep containers closed when not in use. Remove all contaminated clothing immediately and wash. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential - protective skin oils can be dissolved by solvents.

REGULATORY INFORMATION

PRODUCT NAME: EPO-TEK EH100
DATE REVISED: 11/10/11
REV: D

EPOXY TECHNOLOGY
14 FORTUNE DRIVE
BILLERICA, MA 01821
Tel: (978) 667-3805

SARA TITLE III SECTION 313 SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right To Know Act of 1986 (40 CFR 372): Silver Flake as listed above.

1. TSCA Inventory Status

All the components of this product are listed on the TSCA Inventory.

2. RCRA Status

This product contains the following chemicals listed on the 40 CFR Part 261.33: None

3. CERCLA Status

This product contains the following chemicals listed on the 40 CFR Part 302.4: None

4. Transportation

Part A

Not Restricted

Part B

Proper Shipping Name: Amines, Liquid, Corrosive, N.O.S. (Polyoxypropylenediamine)
Hazard Class: 8
Packing Group: III
ID Number: UN2735
Transport Label(s): Corrosive Liquid

The information contained herein is given in good faith. However, no guarantee or warranty of any kind expressed or implied is made with respect to this information.