

MATERIAL SAFETY DATA SHEET**PRODUCT NAME:** Epo Tek H20E-PFC, Part A***HMIS: HEALTH- 2 FIRE-1 REACTIVITY- 0****Carcinogen: NTP (No) IARC (No) OSHA (No)**

* HMIS CODE ratings are estimated by Epoxy Technology.

**EPOXY TECHNOLOGY
14 FORTUNE DRIVE
BILLERICA, MA 01821****EMERGENCY PHONE:**
US/CANADA: 800-255-3924
INT'L COLLECT: + 813-248-0585**DATE REVISED: 11/13/2009
REV: B**

I. IDENTIFICATION & PHYSICAL DATA**PERCENT VOLATILE:** NA
BOILING POINT: NA
VAPOR DENSITY: >Air
APPEARANCE: Silver Paste
ODOR: Mild**VAPOR PRESSURE:** NA
SOLUBILITY IN WATER: Low
EVAPORATION RATE: <BUAC
SPECIFIC GRAVITY: NA

II. HAZARDOUS INGREDIENTS

	CAS#	WT %
Silver Flake	7440-22-4	60-80%
Epoxy Phenol Novolac	28064-14-4	15-35%

III. FIRE & EXPLOSION DATA**FLASH POINT:** >200F**EXTINGUISHING MEDIA:** Dry chemical, foam, carbon dioxide.**UNUSUAL FIRE & EXPLOSION HAZARDS:** Avoid fumes liberated by heat.**SPECIAL FIRE FIGHTING PROCEDURES:** Wear self contained breathing apparatus and complete personal protective equipment. Remove all ignition sources. Use a water spray to cool fire exposed containers.

IV. REACTIVITY DATA**STABILITY:** Stable**HAZARDOUS POLYMERIZATION:** Will not occur.**CONDITIONS TO AVOID:** Excessive heat.**MATERIALS TO AVOID:** Strong oxidizing and reducing agents.**HAZARDOUS DECOMPOSITION PRODUCTS:** Fumes produced when heated to decomposition may include carbon monoxide, and carbon dioxide.

The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guarantee, or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what measures are necessary to safely use this product, either alone or in the combination with other products, and to determine its environmental regulatory compliance obligations under applicable federal or state laws.

V. HEALTH HAZARD DATA

Epo Tek H20E-PFC, Part A

EFFECTS OF OVER EXPOSURE

INGESTION: May cause severe gastric disturbance. May be moderately toxic.

INHALATION: Can cause respiratory irritation. This type of exposure is avoidable with the use of local exhaust ventilation.

SKIN CONTACT: Can cause dermatitis and irritation. This type of exposure can be avoided by the use of local exhaust ventilation, gloves, and chemical splash goggles.

EYE CONTACT: Irritating to the eyes. this type of exposure can be avoided by the use of local exhaust ventilation and chemical splash goggles.

CHRONIC EFFECTS OF OVER EXPOSURE: Can cause dermatitis and sensitization.

EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT: In case of eye contact, flush well with water and get medical attention immediately.

SKIN CONTACT: In case of skin contact, clean with soap and water. Do not use solvents.

INGESTION: If swallowed, get medical attention immediately.

INHALATION: Can be irritating to respiratory tract. This type of exposure is avoidable with positive exhaust ventilation.

VI. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED: Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Absorb spillage with inert material and dispose.

WASTE DISPOSAL METHOD: Incinerate or use hazardous waste treatment procedures that are in accordance with federal, state and local regulations.

VII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear an approved respirator whenever high level exposure to vapors or mist is anticipated.

VENTILATION: Local exhaust recommended for exposure control.

PROTECTIVE GLOVES: Impervious gloves - neoprene or equivalent. A combination of barrier cream and gloves is recommended.

EYE PROTECTION: Chemical splash goggles recommended.

OTHER PROTECTIVE EQUIPMENT: For operations where contact can occur, use a face shield and impervious apron. A safety shower and eye wash facility should be available.

VIII. SPECIAL PRECAUTIONS: Avoid contact with skin and eyes. Avoid breathing vapors. Keep containers closed when not in use. Remove all contaminated clothing immediately and wash. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential - protective skin oils can be dissolved by solvents.

MATERIAL SAFETY DATA SHEET

**EPOXY TECHNOLOGY
14 FORTUNE DRIVE
BILLERICA, MA 01821**

PRODUCT NAME: Epo Tek H20E-PFC, Part B

EMERGENCY PHONE:
US/CANADA: 800-255-3924
INT'L COLLECT: + 813-248-0585

***HMIS: HEALTH- 2 FIRE-1 REACTIVITY- 0**

Carcinogen: NTP (No) IARC (No) OSHA (No)

DATE REVISED: 11/13/2009
REV: B

* HMIS CODE ratings are estimated by Epoxy Technology.

I. IDENTIFICATION & PHYSICAL DATA

PERCENT VOLATILE: NA
BOILING POINT: NA
VAPOR DENSITY: >Air
APPEARANCE: Silver Paste
ODOR: Mild

VAPOR PRESSURE: NA
SOLUBILITY IN WATER: Low
EVAPORATION RATE: <BUAC
SPECIFIC GRAVITY: NA

II. HAZARDOUS INGREDIENTS

CAS#

WT %

Silver Flake

7440-22-4

70-90%

III. FIRE & EXPLOSION DATA

FLASH POINT: >200F

EXTINGUISHING MEDIA: Dry chemical, foam, carbon dioxide.

UNUSUAL FIRE & EXPLOSION HAZARDS: Avoid fumes liberated by heat.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self contained breathing apparatus and complete personal protective equipment. Remove all ignition sources. Use a water spray to cool fire exposed containers.

IV. REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Excessive heat.

MATERIALS TO AVOID: Strong oxidizing and reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Fumes produced when heated to decomposition may include oxides of nitrogen, carbon monoxide, and carbon dioxide.

The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guarantee, or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what measures are necessary to safely use this product, either alone or in the combination with other products, and to determine its environmental regulatory compliance under applicable federal or state laws.

V. HEALTH HAZARD DATA

Epo Tek H20E-PFC, Part B

EFFECTS OF OVER EXPOSURE

INGESTION: Contains materials that may be moderately toxic. Ingestion can severely upset the gastric system.

INHALATION: Can cause respiratory irritation and sensitization. This type of contact can be avoided by the use of local, exhaust ventilation.

SKIN CONTACT: May cause dermatitis and sensitization. This type of exposure is avoidable by the use of local, exhaust ventilation, adequate clothing, gloves and chemical splash goggles.

EYE CONTACT: Irritating to the eyes. Can cause injury. This type of exposure is avoidable by the use of local, exhaust ventilation, adequate clothing, gloves and chemical splash goggles.

CHRONIC EFFECTS OF OVER EXPOSURE: May cause dermatitis and sensitization.

EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT: In event of eye contact, flush well with water and get medical attention immediately.

SKIN CONTACT: In case of skin contact, clean with soap and water. Do not use solvents. Remove contaminated clothing.

INGESTION: Get medical attention immediately.

INHALATION: Can be irritating to respiratory tract.

VI. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED: Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Absorb spillage with inert material and dispose.

WASTE DISPOSAL METHOD: Incinerate or use hazardous waste treatment procedures that are in accordance with federal, state and local regulations.

VII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear a NIOSH approved respirator whenever high level exposure to vapors or mist is anticipated.

VENTILATION: Local exhaust ventilation recommended for exposure control.

PROTECTIVE GLOVES: Impervious gloves - neoprene or equivalent. A combination of barrier cream and gloves is recommended.

EYE PROTECTION: This type of contact can be avoided through the use of Chemical splash goggles.

OTHER PROTECTIVE EQUIPMENT: For operations where contact can occur, use a face shield and impervious apron. A safety shower and eye must be located in close proximity to work and handling areas.

VIII. SPECIAL PRECAUTIONS: Avoid contact with skin and eyes. Avoid breathing vapors. Keep containers closed when not in use. Remove all contaminated clothing immediately and wash. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential - protective skin oils can be dissolved by solvents.

REGULATORY INFORMATION

**EPOXY TECHNOLOGY
14 FORTUNE DRIVE
BILLERICA, MA 01821
TEL: (978) 667 – 3805**

PRODUCT NAME: H20E-PFC
DATE REVISED: 11/13/2009
REV: B

1. SARA TITLE III SECTION 313 SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right To Know Act of 1986 (40 CFR 372): Silver Flake as listed above.

2. TSCA Inventory Status

All the components of this product are listed on the TSCA Inventory.

3. RCRA Status

This product contains the following chemicals listed on the 40 CFR Part 261.33: None

4. CERCLA Status

This product contains the following chemicals listed on the 40 CFR Part 302.4: None

5. Transportation

Part A

Not Restricted

Part B

Not Restricted .

The information contained herein is given in good faith. However, no guarantee or warranty of any kind expressed or implied is made with respect to this information.