



SAFETY DATA SHEET EPO-TEK® EJ2312 Part A

1. Identification

Product identifier

Product name EPO-TEK® EJ2312 Part A

Product number EJ2312/A

Recommended use of the chemical and restrictions on use

Application Adhesive.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.
14 Fortune Drive
Billerica, MA 01821
USA
(978) 667-3805
(978) 663-9782
www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

Label elements

Pictogram



Signal word

Danger

Hazard statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P302+P352 If on skin: Wash with plenty of water.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P501 Dispose of contents/ container in accordance with national regulations.

EPO-TEK® EJ2312 Part A

Contains Epoxy Phenol Novolac, Reactive Diluent

Other hazards

Harmful dust may be released during cutting or grinding process.

Hazards not otherwise classified (HNOC) Contains epoxy constituents. May produce an allergic reaction.

3. Composition/information on ingredients

Mixtures

Silver	60-100%
CAS number: 7440-22-4	
Classification	
Aquatic Chronic 2 - H411	
Epoxy Phenol Novolac	10-30%
CAS number: 9003-36-5	
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
Reactive Diluent	5-10%
CAS number: Proprietary	
Classification	
Acute Tox. 4 - H302	
Eye Dam. 1 - H318	
STOT SE 3 - H336	

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin Contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation of dusts during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.
-------------------	------------------------------------------------------------------------------------------------------------------------

EPO-TEK® EJ2312 Part A

Ingestion	May cause discomfort if swallowed.
Skin contact	Causes skin irritation. May cause sensitisation by skin contact.
Eye contact	Causes serious eye damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Dry chemicals. Foam. Carbon dioxide (CO ₂).
-------------------------------------	----------------------------------------------------------------------------------------------

Special hazards arising from the substance or mixture

Hazardous combustion products	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.
--------------------------------------	-------------------------------------------------------------------------------------------------------------------

Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapors.
-----------------------------------------------	---------------------------------------

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
------------------------------------------------------	-------------------------------------------------------------------------------------------------------

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	-------------------------------------------------------------------------------

Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground. Avoid release to the environment.
----------------------------------	----------------------------------------------------------------------------------------------------

Methods and material for containment and cleaning up

Methods for cleaning up	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.
--------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Reference to other sections	For personal protection, see Section 8.
------------------------------------	-----------------------------------------

7. Handling and storage

Precautions for safe handling

Usage precautions	Avoid spilling. Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Do not eat, drink or smoke when using the product. Avoid inhalation of vapors.
--------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Advice on general occupational hygiene	Provide eyewash station. Do not eat, drink or smoke when using this product. Wash promptly with soap and water if skin becomes contaminated.
-----------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------

Conditions for safe storage, including any incompatibilities

Storage precautions	Store at room temperature. Keep container tightly sealed when not in use.
----------------------------	---------------------------------------------------------------------------

Storage class	Chemical storage.
----------------------	-------------------

Specific end uses(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.
----------------------------	-----------------------------------------------------------------

EPO-TEK® EJ2312 Part A

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Silver

Long-term exposure limit (8-hour TWA): 0.1

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Paste.
Color	Silver.
Odor	Mild.
Flash point	> 93°C
Evaporation rate	<BuAc
Vapor density	>1
Solubility(ies)	Slightly soluble in water.
Other information	None.

10. Stability and reactivity

Reactivity

The following materials may react with the product: Strong oxidizing agents. Strong reducing agents.

Stability

Stable at normal ambient temperatures.

Possibility of hazardous reactions

Will not polymerize.

EPO-TEK® EJ2312 Part A

Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of ignition.
Materials to avoid	Strong oxidizing agents. Strong reducing agents.
Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO ₂).

11. Toxicological information

Information on toxicological effects

Inhalation	Inhalation of dusts during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.
Ingestion	May cause discomfort if swallowed.
Skin Contact	May cause sensitisation by skin contact. Irritating to skin.
Eye contact	Causes serious eye damage.

12. Ecological Information

Ecotoxicity	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Toxicity	Very toxic to aquatic organisms.
<u>Persistence and degradability</u>	
Persistence and degradability	No data available.
<u>Bioaccumulative potential</u>	
Bio-Accumulative Potential	No data available on bioaccumulation.
<u>Mobility in soil</u>	
Mobility	The product has poor water-solubility.
<u>Other adverse effects</u>	
Other adverse effects	Not known.

13. Disposal considerations

Waste treatment methods

Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
-------------------------	-----------------------------------------------------------------------------------------------------------------------------

14. Transport information

UN Number

UN No. (TDG)	3082
UN No. (IMDG)	3082
UN No. (ICAO)	3082
UN No. (DOT)	UN3082

EPO-TEK® EJ2312 Part A

UN proper shipping name

Proper shipping name (TDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Silver, Epoxy Phenol Novolac)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Silver, Epoxy Phenol Novolac)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Silver, Epoxy Phenol Novolac)

Proper shipping name (DOT) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Silver, Epoxy Phenol Novolac)

Transport hazard class(es)

TDG class 9

TDG label(s) 9

IMDG Class 9

ICAO class/division 9

Transport labels



Packing group

TDG Packing Group III

IMDG packing group III

ICAO packing group III

DOT packing group III

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

EmS F-A, S-F

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are required to be listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed:

EPO-TEK® EJ2312 Part A

Silver

1,000 lbs (454 Kg)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are required to be listed.

SARA 313 Emission Reporting

The following ingredients are listed:

Silver

CAA Accidental Release Prevention

None of the ingredients are required to be listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are required to be listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are required to be listed.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed:

Silver

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are required to be listed.

Massachusetts "Right To Know" List

The following ingredients are listed:

Silver

Rhode Island "Right To Know" List

The following ingredients are listed:

Silver

Minnesota "Right To Know" List

The following ingredients are listed:

Silver

New Jersey "Right To Know" List

The following ingredients are listed:

Silver

Pennsylvania "Right To Know" List

The following ingredients are listed:

Silver

Inventories

EU - EINECS/ELINCS

Some of the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

EPO-TEK® EJ2312 Part A

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed.

Australia - AICS

Some of the ingredients are listed or exempt.

Japan - MITI

Some of the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

Some of the ingredients are listed or exempt.

16. Other information

Revision date	6/19/2017
Revision	1
Supersedes date	12/11/2014
Hazard statements in full	<p>H302 Harmful if swallowed.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H318 Causes serious eye damage.</p> <p>H319 Causes serious eye irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p>

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.



SAFETY DATA SHEET EPO-TEK® EJ2312 Part B

1. Identification

Product identifier

Product name EPO-TEK® EJ2312 Part B

Product number EJ2312/B

Recommended use of the chemical and restrictions on use

Application Adhesive.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.
14 Fortune Drive
Billerica, MA 01821
USA
(978) 667-3805
(978) 663-9782
www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H332 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Repr. 2 - H361fd STOT SE 3 - H335

Environmental hazards Aquatic Chronic 3 - H412

Human health

Contains a substance/a group of substances which may impair fertility. Contains a substance/a group of substances which may damage the unborn child.

Label elements

Pictogram



Signal word

Danger

Hazard statements

H302+H332 Harmful if swallowed or if inhaled.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H412 Harmful to aquatic life with long lasting effects.

EPO-TEK® EJ2312 Part B

Precautionary statements	<p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.</p> <p>P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.</p> <p>P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Contains	Cycloaliphatic Diamine, Accelerating Agent, Substituted Aromatic Compound

3. Composition/information on ingredients

Mixtures

Cycloaliphatic Diamine	30-60%
CAS number: Proprietary	
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
Aquatic Chronic 3 - H412	
Accelerating Agent	30-60%
CAS number: Proprietary	
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H332	
Substituted Aromatic Compound	10-30%
CAS number: Proprietary	
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Repr. 2 - H361fd	
STOT SE 3 - H335	

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin Contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

EPO-TEK® EJ2312 Part B

Eye contact Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

Most important symptoms and effects, both acute and delayed

Inhalation Vapors may cause headache, fatigue, dizziness and nausea. Irritation of nose, throat and airway. Upper respiratory irritation.

Ingestion May cause chemical burns in mouth and throat. May cause stomach pain or vomiting.

Skin contact Allergic rash. Severe irritation. Burns can occur. Blistering may occur.

Eye contact Severe irritation, burning and tearing. Corneal damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Dry chemicals. Foam. Carbon dioxide (CO₂).

Special hazards arising from the substance or mixture

Hazardous combustion products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapors.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Avoid discharge to the aquatic environment.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

Reference to other sections For personal protection, see Section 8.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Do not handle broken packages without protective equipment. Do not eat, drink or smoke when using the product. Avoid inhalation of vapors. Provide adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage precautions Store at room temperature. Keep container tightly sealed when not in use.

Storage class Chemical storage.

EPO-TEK® EJ2312 Part B

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Ingredient comments No exposure limits known for ingredient(s).

Exposure controls

Protective equipment



Appropriate engineering controls Provide adequate general and local exhaust ventilation.

Eye/face protection Wear tight-fitting, chemical splash goggles or face shield.

Hand protection Wear protective gloves.

Other skin and body protection Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Liquid.

Color Yellow.

Odor Mild.

Flash point > 93°C

Evaporation rate <BuAc

Vapor density >1

Other information None.

10. Stability and reactivity

Reactivity The following materials may react with the product: Strong oxidizing agents. Strong reducing agents.

Stability Stable at normal ambient temperatures and when used as recommended.

Possibility of hazardous reactions Will not polymerize.

Conditions to avoid Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of ignition.

EPO-TEK® EJ2312 Part B

Materials to avoid	Strong oxidizing agents. Strong reducing agents.
Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. Oxides of carbon. Oxides of nitrogen.

11. Toxicological information

Information on toxicological effects

Inhalation	Irritating to respiratory system. Harmful by inhalation.
Ingestion	Harmful if swallowed. May cause stomach pain or vomiting. Causes burns.
Skin Contact	May cause sensitisation by skin contact. Harmful in contact with skin. Causes burns.
Eye contact	Severe irritation, burning and tearing. A single exposure may cause the following adverse effects: Corneal damage. Causes burns.

12. Ecological Information

Ecotoxicity	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
--------------------	-----------------------------------------------------------------------------------------------

Persistence and degradability

Persistence and degradability	No data available.
--------------------------------------	--------------------

Bioaccumulative potential

Bio-Accumulative Potential	No data available on bioaccumulation.
-----------------------------------	---------------------------------------

Mobility in soil

Mobility	No data available.
-----------------	--------------------

Other adverse effects

Other adverse effects	Not known.
------------------------------	------------

13. Disposal considerations

Waste treatment methods

Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
-------------------------	-----------------------------------------------------------------------------------------------------------------------------

EPO-TEK® EJ2312 Part B

14. Transport information

UN Number

UN No. (TDG)	2735
UN No. (IMDG)	2735
UN No. (ICAO)	2735
UN No. (DOT)	UN2735

UN proper shipping name

Proper shipping name (TDG) AMINES, LIQUID, CORROSIVE, N.O.S. (Cycloaliphatic Diamine)

Proper shipping name (IMDG) AMINES, LIQUID, CORROSIVE, N.O.S. (Cycloaliphatic Diamine)

Proper shipping name (ICAO) AMINES, LIQUID, CORROSIVE, N.O.S. (Cycloaliphatic Diamine)

Proper shipping name (DOT) AMINES, LIQUID, CORROSIVE, N.O.S. (Cycloaliphatic Diamine)

Transport hazard class(es)

DOT hazard class	8
DOT hazard label	8
TDG class	8
TDG label(s)	8
IMDG Class	8
ICAO class/division	8

Transport labels



DOT transport labels



Packing group

TDG Packing Group	III
IMDG packing group	III
ICAO packing group	III
DOT packing group	III

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

EmS F-A, S-B

EPO-TEK® EJ2312 Part B

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Regulatory References Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of Intellectual Property Rights (TRIPS), Section 7, Art. 39.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are required to be listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are required to be listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are required to be listed.

SARA 313 Emission Reporting

None of the ingredients are required to be listed.

CAA Accidental Release Prevention

None of the ingredients are required to be listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are required to be listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are required to be listed.

California Air Toxics "Hot Spots" (A-I)

None of the ingredients are required to be listed.

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are required to be listed.

Massachusetts "Right To Know" List

The following ingredients are listed:

Accelerating Agent

Rhode Island "Right To Know" List

None of the ingredients are required to be listed.

Minnesota "Right To Know" List

The following ingredients are listed:

Accelerating Agent

New Jersey "Right To Know" List

The following ingredients are listed:

Cycloaliphatic Diamine

Pennsylvania "Right To Know" List

The following ingredients are listed:

EPO-TEK® EJ2312 Part B

Accelerating Agent

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed.

Australia - AICS

All the ingredients are listed or exempt.

Japan - MITI

All the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

All the ingredients are listed or exempt.

16. Other information

Revision date	6/19/2017
Revision	2
Supersedes date	12/11/2014
Hazard statements in full	<p>H302 Harmful if swallowed.</p> <p>H312 Harmful in contact with skin.</p> <p>H314 Causes severe skin burns and eye damage.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H318 Causes serious eye damage.</p> <p>H319 Causes serious eye irritation.</p> <p>H332 Harmful if inhaled.</p> <p>H335 May cause respiratory irritation.</p> <p>H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.