



SAFETY DATA SHEET EPO-TEK® 730 Black Part A

1. Identification

Product identifier

Product name EPO-TEK® 730 Black Part A

Product number 730 Black/A

Recommended use of the chemical and restrictions on use

Application Adhesive.

Uses advised against Use only for intended applications.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.
14 Fortune Drive
Billerica, MA 01821
USA
(978) 667-3805
(978) 663-9782
www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone ChemTel: +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status This Product is Hazardous under the OSHA Hazard Communication Standard.


Physical hazards Not Classified

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 1 - H370

Environmental hazards Aquatic Chronic 2 - H411

Label elements

Pictogram



Signal word

Danger

Hazard statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H332 Harmful if inhaled.
H370 Causes damage to organs .
H411 Toxic to aquatic life with long lasting effects.

EPO-TEK® 730 Black Part A

Precautionary statements P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 If on skin: Wash with plenty of water.
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains Epoxy Resin, Epoxy Resin Blend, Reactive Diluent, Reactive Diluent, Polar Activator

Other hazards

Harmful dust may be released during cutting or grinding process.

3. Composition/information on ingredients

Substances

Epoxy Resin	30-60%
CAS number: Proprietary	
Classification	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
Epoxy Resin Blend	10-30%
CAS number: Proprietary	
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
Reactive Diluent	10-30%
CAS number: Proprietary	
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
Reactive Diluent	1-5%
CAS number: Proprietary	
Classification	
Acute Tox. 4 - H302	
Eye Dam. 1 - H318	
STOT SE 3 - H336	

EPO-TEK® 730 Black Part A

Polar Activator	1-5%
CAS number: Proprietary	
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 3 - H301	
Acute Tox. 3 - H311	
Acute Tox. 3 - H331	
STOT SE 1 - H370	
Carbon Black	<1%
CAS number: 1333-86-4	
Classification	
Carc. 2 - H351	

The full text for all hazard statements is displayed in Section 16.

Product name	EPO-TEK® 730 Black Part A
Ingredient notes	The exact percentage/concentration is withheld as a trade secret in accordance with 29 CFR 1910.1200. The exact identity is withheld as a trade secret in accordance with 29 CFR 1910.1200.
Composition comments	This product contains Carbon Black, which is suspected of causing cancer when inhaled in fine particulate form. Carbon Black should not be respirable in this formulation. However, if cured material will be ground, milled, etc., wear respiratory protection to avoid inhaling any dust that may be produced.

4. First-aid measures

Description of first aid measures

Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin Contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

Most important symptoms and effects, both acute and delayed

Inhalation	Harmful if inhaled. Vapors may cause headache, fatigue, dizziness and nausea. Irritation of nose, throat and airway. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.
Ingestion	May cause discomfort if swallowed.
Skin contact	Skin irritation. Allergic rash.
Eye contact	Causes serious eye damage. Severe irritation, burning and tearing.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

EPO-TEK® 730 Black Part A

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Dry chemicals. Foam. Carbon dioxide (CO₂).

Special hazards arising from the substance or mixture

Hazardous combustion products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapors.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Avoid release to the environment.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

Reference to other sections For personal protection, see Section 8.

7. Handling and storage

Precautions for safe handling

Usage precautions Handle all packages and containers carefully to minimize spills. Avoid inhalation of vapors and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet.

Advice on general occupational hygiene Provide eyewash station. Do not eat, drink or smoke when using this product. Wash promptly if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin.

Conditions for safe storage, including any incompatibilities

Storage precautions Store at room temperature. Keep container tightly sealed when not in use.

Storage class Chemical storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Polar Activator

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm

Short-term exposure limit (15-minute): ACGIH 250 ppm

EPO-TEK® 730 Black Part A

Carbon Black

Long-term exposure limit (8-hour TWA): ACGIH 3 mg/m³ inhalable fraction

Long-term exposure limit (8-hour TWA): 3

A3

Long-term exposure limit (8-hour TWA): OSHA 3.5 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

OSHA = Occupational Safety and Health Administration.

Ingredient comments

*This product contains Carbon Black, which is suspected of causing cancer when inhaled in fine particulate form. Carbon Black should not be respirable in this formulation. However, if cured material will be ground, milled, etc., wear respiratory protection to avoid inhaling any dust that may be produced.

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

Wear protective gloves. It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Paste.
Color	Black.
Odor	Mild.
Odor threshold	No specific test data are available.
pH	No specific test data are available.
Melting point	No specific test data are available.
Initial boiling point and range	No specific test data are available.
Flash point	> 93°C
Evaporation rate	<BuAc
Upper/lower flammability or explosive limits	No specific test data are available.

EPO-TEK® 730 Black Part A

Vapor pressure	No specific test data are available.
Vapor density	> 1
Relative density	No specific test data are available.
Solubility(ies)	Slightly soluble in water.
Partition coefficient	No specific test data are available.
Auto-ignition temperature	No specific test data are available.
Decomposition Temperature	No specific test data are available.
Viscosity	No specific test data are available.
Other information	None.

10. Stability and reactivity

Reactivity	The following materials may react with the product: Strong oxidizing agents. Strong reducing agents.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	Will not polymerize.
Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of ignition.
Materials to avoid	Strong oxidizing agents. Strong reducing agents.
Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 2,235.64

Acute toxicity - dermal

ATE dermal (mg/kg) 6,173.9

Acute toxicity - inhalation

ATE inhalation (gases ppm) 19,948.02

ATE inhalation (vapours mg/l) 61.74

ATE inhalation (dusts/mists mg/l) 2.52

Carcinogenicity

Carcinogenicity *This product contains Carbon Black, which is suspected of causing cancer when inhaled in fine particulate form. Carbon Black should not be respirable in this formulation. However, if cured material will be ground, milled, etc., wear respiratory protection to avoid inhaling any dust that may be produced.

EPO-TEK® 730 Black Part A

Inhalation	Irritating to respiratory system. Harmful by inhalation.
Ingestion	May cause discomfort if swallowed.
Skin Contact	May cause sensitisation by skin contact. Irritating to skin. Harmful in contact with skin.
Eye contact	Irritating to eyes.

Toxicological information on ingredients.

Carbon Black

Carcinogenicity

IARC carcinogenicity IARC Group 2B Possibly carcinogenic to humans.

NTP carcinogenicity Reasonably anticipated to be a human carcinogen.

OSHA Carcinogenicity Not listed.

12. Ecological Information

Ecotoxicity Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Acute aquatic toxicity

Acute toxicity - fish Not available.

Persistence and degradability

Persistence and degradability No data available.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient No specific test data are available.

Mobility in soil

Mobility The product has poor water-solubility.

Other adverse effects

Other adverse effects Not known.

13. Disposal considerations

Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

UN Number

UN No. (TDG) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

UN No. (DOT) UN3082

UN proper shipping name

Proper shipping name (TDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Resin Blend)

EPO-TEK® 730 Black Part A

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Resin Blend)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Resin Blend)

Proper shipping name (DOT) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Resin Blend)

Transport hazard class(es)

DOT hazard class 9

DOT hazard label 9

TDG class 9

TDG label(s) 9

IMDG Class 9

ICAO class/division 9

Transport labels



DOT transport labels



Packing group

TDG Packing Group III

IMDG packing group III

ICAO packing group III

DOT packing group III

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

EmS F-A, S-F

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Regulatory References Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of Intellectual Property Rights (TRIPS), Section 7, Art. 39.

EPO-TEK® 730 Black Part A

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed:

Polar Activator

5,000 lbs (2270 Kg)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed.

SARA 313 Emission Reporting

The following ingredients are listed:

Polar Activator

1-5%

CAA Accidental Release Prevention

None of the ingredients are listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

WARNING: This product contains a substance known to the State of California to cause cancer and/or reproductive harm.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed:

Polar Activator

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed.

Massachusetts "Right To Know" List

The following ingredients are listed:

Carbon Black

Polar Activator

Rhode Island "Right To Know" List

The following ingredients are listed:

Carbon Black

Polar Activator

Minnesota "Right To Know" List

The following ingredients are listed:

Carbon Black

Polar Activator

New Jersey "Right To Know" List

The following ingredients are listed:

Carbon Black

EPO-TEK® 730 Black Part A

Polar Activator

Pennsylvania "Right To Know" List

The following ingredients are listed:

Carbon Black

Polar Activator

Inventories

EU - EINECS/ELINCS

Some of the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed.

Australia - AICS

All the ingredients are listed or exempt.

Japan - MITI

Some of the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

All the ingredients are listed or exempt.

16. Other information

Revision date	7/3/2018
Revision	2
Supersedes date	8/28/2014

EPO-TEK® 730 Black Part A

Hazard statements in full

H225 Highly flammable liquid and vapor.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H370 Causes damage to organs .
H411 Toxic to aquatic life with long lasting effects.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.



SAFETY DATA SHEET EPO-TEK® 730 Black Part B

1. Identification

Product identifier

Product name EPO-TEK® 730 Black Part B
Product number 730 Black/B

Recommended use of the chemical and restrictions on use

Application Adhesive.
Uses advised against Use only for intended applications.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.
14 Fortune Drive
Billerica, MA 01821
USA
(978) 667-3805
(978) 663-9782
www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone ChemTel: +1 (800) 255-3924, +1 (813) 248-0585


2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified
Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Skin Sens. 1 - H317 STOT SE 1 - H370
Environmental hazards Not Classified

Label elements

Pictogram



Signal word Danger

Hazard statements H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H370 Causes damage to organs .

EPO-TEK® 730 Black Part B

Precautionary statements

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 If on skin: Wash with plenty of water.
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains Polyamide Resin, Curing Agent, Polar Activator

Other hazards

Harmful dust may be released during cutting or grinding process.

3. Composition/information on ingredients

Substances

Polyamide Resin	60-100%
CAS number: Proprietary	
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Curing Agent	1-5%
CAS number: Proprietary	
Classification	
Acute Tox. 4 - H312	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
Aquatic Chronic 3 - H412	
Polar Activator	1-5%
CAS number: Proprietary	
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 3 - H301	
Acute Tox. 3 - H311	
Acute Tox. 3 - H331	
STOT SE 1 - H370	

The full text for all hazard statements is displayed in Section 16.

Product name EPO-TEK® 730 Black Part B

4. First-aid measures

Description of first aid measures

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

EPO-TEK® 730 Black Part B

Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. Do not induce vomiting. Remove affected person from source of contamination. Give plenty of water to drink. Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Skin Contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

Most important symptoms and effects, both acute and delayed

General information	Causes damage to organs .
Inhalation	Harmful if inhaled. Vapors may cause headache, fatigue, dizziness and nausea. Inhalation of dusts during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.
Ingestion	May cause discomfort if swallowed.
Skin contact	Causes skin irritation. May cause sensitisation by skin contact.
Eye contact	Causes serious eye irritation.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Dry chemicals. Foam. Carbon dioxide (CO₂).

Special hazards arising from the substance or mixture

Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.
Advice for firefighters	
Protective actions during firefighting	Avoid breathing fire gases or vapors.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Avoid release to the environment.

Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses.

Reference to other sections For personal protection, see Section 8.

EPO-TEK® 730 Black Part B

7. Handling and storage

Precautions for safe handling

Usage precautions Handle all packages and containers carefully to minimize spills. Avoid inhalation of vapors and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Wash promptly if skin becomes contaminated. Wash contaminated clothing before reuse. Use appropriate skin cream to prevent drying of skin.

Conditions for safe storage, including any incompatibilities

Storage precautions Store at room temperature. Keep container tightly sealed when not in use.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Polar Activator

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm

Short-term exposure limit (15-minute): ACGIH 250 ppm

ACGIH = American Conference of Governmental Industrial Hygienists.

Exposure controls

Protective equipment



Appropriate engineering controls Provide adequate general and local exhaust ventilation.

Eye/face protection Wear tight-fitting, chemical splash goggles or face shield.

Hand protection It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body protection Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

Hygiene measures Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Paste.

Color Tan.

Odor Mild.

Odor threshold No specific test data are available.

EPO-TEK® 730 Black Part B

pH	No specific test data are available.
Melting point	No specific test data are available.
Initial boiling point and range	No specific test data are available.
Flash point	> 185°C
Evaporation rate	<BuAc
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	No specific test data are available.
Vapor pressure	No specific test data are available.
Vapor density	>1
Bulk density	No specific test data are available.
Solubility(ies)	Slightly soluble in water.
Partition coefficient	No specific test data are available.
Auto-ignition temperature	No specific test data are available.
Decomposition Temperature	No specific test data are available.
Viscosity	No specific test data are available.
Other information	Not available.

10. Stability and reactivity

Reactivity	The following materials may react with the product: Strong oxidizing agents. Strong reducing agents.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	Will not polymerize.
Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of ignition.
Materials to avoid	Strong oxidizing agents. Strong reducing agents.
Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Oxides of nitrogen.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 2,406.79

Acute toxicity - dermal

ATE dermal (mg/kg) 5,657.14

Acute toxicity - inhalation

ATE inhalation (gases ppm) 16,847.5

EPO-TEK® 730 Black Part B

ATE inhalation (vapours mg/l)	72.2
ATE inhalation (dusts/mists mg/l)	12.03
Inhalation	Harmful if inhaled. Vapors may cause headache, fatigue, dizziness and nausea.
Ingestion	May cause discomfort if swallowed.
Skin Contact	Causes skin irritation. May cause sensitisation by skin contact.
Eye contact	Causes serious eye irritation.
Acute and chronic health hazards	Causes damage to organs .
Target Organs	Skin Eyes Respiratory system, lungs

12. Ecological Information

Ecotoxicity	There are no data on the ecotoxicity of this product.
<u>Persistence and degradability</u>	
Persistence and degradability	There are no data on the degradability of this product.
<u>Bioaccumulative potential</u>	
Bio-Accumulative Potential	No data available on bioaccumulation.
Partition coefficient	No specific test data are available.
<u>Mobility in soil</u>	
Mobility	The product has poor water-solubility.
<u>Other adverse effects</u>	
Other adverse effects	Not known.

13. Disposal considerations

Waste treatment methods

Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
-------------------------	---

14. Transport information

General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).
<u>UN Number</u>	
Not applicable.	
UN No. (DOT)	Not applicable.
<u>UN proper shipping name</u>	
Not applicable.	
Proper shipping name (DOT)	Not applicable.
<u>Transport hazard class(es)</u>	
No transport warning sign required.	

EPO-TEK® 730 Black Part B

DOT transport labels

No transport warning sign required.

Packing group

Not applicable.

DOT packing group Not applicable.

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

Not applicable.

DOT reportable quantity Not applicable.

DOT TIH Zone Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Regulatory References Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of Intellectual Property Rights (TRIPS), Section 7, Art. 39.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed:

Polar Activator

5,000 lbs (2270 Kg)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed.

SARA 313 Emission Reporting

The following ingredients are listed:

Polar Activator

1-5%

CAA Accidental Release Prevention

None of the ingredients are listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed.

EPO-TEK® 730 Black Part B

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed:

Polar Activator

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed.

Massachusetts "Right To Know" List

The following ingredients are listed:

Polar Activator

Curing Agent

Rhode Island "Right To Know" List

The following ingredients are listed:

Polar Activator

Minnesota "Right To Know" List

The following ingredients are listed:

Polar Activator

New Jersey "Right To Know" List

The following ingredients are listed:

Polar Activator

Curing Agent

Pennsylvania "Right To Know" List

The following ingredients are listed:

Polar Activator

Curing Agent

Inventories

EU - EINECS/ELINCS

Some of the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed.

Australia - AICS

All the ingredients are listed or exempt.

Japan - MITI

Some of the ingredients are listed or exempt.

Korea - KECI

Some of the ingredients are listed or exempt.

EPO-TEK® 730 Black Part B

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

Some of the ingredients are listed or exempt.

16. Other information

Revision date	7/3/2018
Revision	2
Supersedes date	8/28/2014
Hazard statements in full	H225 Highly flammable liquid and vapor. H301 Toxic if swallowed. H311 Toxic in contact with skin. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H370 Causes damage to organs . H412 Harmful to aquatic life with long lasting effects.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.