

SAFETY DATA SHEET EPO-TEK EJ1135

1. Identification

Product identifier

Product name EPO-TEK EJ1135

Product number EJ1135

Recommended use of the chemical and restrictions on use

Application Adhesive.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.

14 Fortune Drive Billerica, MA 01821

USA

(978) 667-3805 (978) 663-9782

www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Carc. 2 - H351

Environmental hazards Aquatic Chronic 2 - H411

Label elements

Pictogram









Signal word

ord Danger

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H351 Suspected of causing cancer.

H411 Toxic to aquatic life with long lasting effects.

EPO-TEK EJ1135

Precautionary statements P280 Wear protective gloves/ protective clothing/ eye protection.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/ container in accordance with national regulations.

Silver, Epoxy Resin Blend, Reactive Diluent, Accelerator

Other hazards

Contains

Hazards not otherwise classified (HNOC)

Contains epoxy constituents. May produce an allergic reaction.

3. Composition/information on ingredients

Mixtures

Silver 60-100%

CAS number: 7440-22-4

Classification

Aquatic Chronic 2 - H411

Epoxy Resin Blend 10-30%

CAS number: Proprietary

Classification

Skin Irrit. 2 - H315

Eye Irrit. 2 - H319

Skin Sens. 1 - H317

Aquatic Chronic 2 - H411

Reactive Diluent 1-5%

CAS number: Proprietary

Classification

Acute Tox. 4 - H302

Acute Tox. 4 - H312

Acute Tox. 4 - H332

Skin Irrit. 2 - H315

Eye Dam. 1 - H318

Skin Sens. 1 - H317

Accelerator <1%

CAS number: Proprietary

Classification

Acute Tox. 4 - H302

Carc. 2 - H351

Aquatic Chronic 1 - H410

EPO-TEK EJ1135

The Full Text for all Hazard Statements are Displayed in Section 16.

4. First-aid measures

Description of first aid measures

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. When breathing is difficult, properly trained personnel may assist affected person

by administering oxygen. Get medical attention if symptoms are severe or persist.

Ingestion Rinse nose and mouth with water. Give plenty of water to drink. Never give anything by mouth

to an unconscious person. Do not induce vomiting unless under the direction of medical

personnel. Get medical attention if symptoms are severe or persist.

Skin Contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Get medical attention if any discomfort continues.

Most important symptoms and effects, both acute and delayed

General information Contains a substance which may be potentially carcinogenic.

Inhalation Inhalation of dust during cutting, grinding or sanding operations involving this product may

cause irritation of the respiratory tract. Gas or vapor in high concentrations may irritate the

respiratory system.

Ingestion May cause discomfort if swallowed.

Skin contact Causes skin irritation. May cause sensitisation by skin contact.

Eye contact Causes serious eye damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Dry chemicals. Foam. Carbon dioxide (CO2).

Special hazards arising from the substance or mixture

Hazardous combustion

Thermal decomposition or combustion products may include the following substances:

Carbon monoxide (CO). Carbon dioxide (CO2).

Advice for firefighters

products

firefighting

Protective actions during

Avoid breathing fire gases or vapors. Use water to keep fire exposed containers cool and

disperse vapors.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Avoid release to the

environment.

EPO-TEK EJ1135

Methods and material for containment and cleaning up

Methods for cleaning up Provide adequate ventilation. Wear suitable protective equipment, including gloves,

goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb in vermiculite,

dry sand or earth and place into containers.

Reference to other sections For personal protection, see Section 8.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Wear protective clothing as described in

Section 8 of this safety data sheet.

Advice on general occupational hygiene

Provide eyewash station. Do not eat, drink or smoke when using this product. Wash promptly with soap and water if skin becomes contaminated. Wash after use and before eating,

smoking and using the toilet. Wash contaminated clothing before reuse. Use appropriate skin

cream to prevent drying of skin.

Conditions for safe storage, including any incompatibilities

Storage precautions Store at -40 degrees C. Keep container tightly sealed when not in use.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Silver

Long-term exposure limit (8-hour TWA): 0.1

Accelerator

Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.

Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate general and local exhaust ventilation.

Eye/face protection Wear tight-fitting, chemical splash goggles or face shield.

Hand protection It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapor contact.

Hygiene measures Do not smoke in work area. Wash hands at the end of each work shift and before eating,

smoking and using the toilet. Wash promptly with soap and water if skin becomes

contaminated. Promptly remove any clothing that becomes contaminated. When using do not

eat, drink or smoke.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

EPO-TEK EJ1135

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Paste.

Color Grey. Dark.

Odor Mild.

Flash point > 93°C

Evaporation rate < BuAc

Vapor density > Air

Solubility(ies) Slightly soluble in water.

Other information None.

10. Stability and reactivity

Reactivity The following materials may react with the product: Strong oxidizing agents. Strong reducing

agents.

Stable at normal ambient temperatures and when used as recommended.

Possibility of hazardous

reactions

Will not polymerize.

Conditions to avoid Avoid heat, flames and other sources of ignition.

Materials to avoid Strong oxidizing agents. Strong reducing agents.

Hazardous decomposition

products

Thermal decomposition or combustion products may include the following substances:

Carbon dioxide (CO2). Carbon monoxide (CO).

11. Toxicological information

Information on toxicological effects

Inhalation Inhalation of dust during cutting, grinding or sanding operations involving this product may

cause irritation of the respiratory tract. Gas or vapor in high concentrations may irritate the

respiratory system.

Ingestion May cause discomfort if swallowed.

Skin Contact Causes skin irritation.

EPO-TEK EJ1135

Eye contact Causes serious eye damage.

Acute and chronic health

hazards

Contains a substance which may be potentially carcinogenic.

12. Ecological Information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Toxicity

Acute toxicity - fish Not available.

Persistence and degradability

Persistence and degradability No data available.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Mobility in soil

Mobility No data available.

Other adverse effects

Other adverse effects Not known.

13. Disposal considerations

Waste treatment methods

General information Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

14. Transport information

UN Number

UN No. (TDG) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

UN No. (DOT) UN3082

UN proper shipping name

Proper shipping name (TDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Silver,

Epoxy Resin Blend)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Silver,

Epoxy Resin Blend)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Silver,

Epoxy Resin Blend)

Proper shipping name (DOT) ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Silver,

Epoxy Resin Blend)

Transport hazard class(es)

DOT hazard class 9

DOT hazard label 9

EPO-TEK EJ1135

TDG class 9
TDG label(s) 9
IMDG Class 9
ICAO class/division 9

Transport labels



DOT transport labels

Packing group

TDG Packing Group III
IMDG packing group III
ICAO packing group III
DOT packing group III

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

EmS F-A, S-F

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

Regulatory ReferencesProprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of Intellectual Property Rights (TRIPS), Section 7, Art. 39.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are required to be listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed or exempt:

Accelerator

100 lbs (45.4 Kg)

Silver

1,000 lbs (454 Kg)

EPO-TEK EJ1135

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are required to be listed.

SARA 313 Emission Reporting

The following ingredients are listed or exempt:

Silver

CAA Accidental Release Prevention

None of the ingredients are required to be listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are required to be listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

WARNING: This product contains a substance known to the State of California to cause cancer and/or reproductive harm.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

Silver

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are required to be listed.

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

Accelerator

Silver

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

Accelerator

Silver

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

Accelerator

Silver

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

Accelerator

Silver

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

Accelerator

Silver

Inventories

EU-EINECS/ELINCS

Some of the ingredients are listed or exempt.

EPO-TEK EJ1135

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US-TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

Australia - AICS

Some of the ingredients are listed or exempt.

Japan - MITI

Some of the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

Some of the ingredients are listed or exempt.

Philippines - PICCS

Some of the ingredients are listed or exempt.

16. Other information

Revision date 7/20/2016

Revision 1

Hazard statements in full H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H351 Suspected of causing cancer.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.