

SAFETY DATA SHEET EPO-TEK® EK1000-1

1. Identification

Product identifier

Product name EPO-TEK® EK1000-1

Product number EK1000-1

Recommended use of the chemical and restrictions on use

Application Adhesive.

Uses advised against Use only for intended applications.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.

14 Fortune Drive Billerica, MA 01821

USA

(978) 667-3805 (978) 663-9782

www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone ChemTel: +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Label elements

Hazard symbols







Signal word Danger

Hazard statements H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

EPO-TEK® EK1000-1

Precautionary statements P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/ shower.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/ container in accordance with national regulations.

Contains Epoxy Phenol Novolac, Diluent

3. Composition/information on ingredients

Mixtures

Silver 60-100%

CAS number: 7440-22-4

M factor (Acute) = 1000 M factor (Chronic) = 100

Classification

Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Epoxy Phenol Novolac 5-10%

CAS number: 9003-36-5

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

Diluent 5-10%

CAS number: Proprietary

Classification

Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Corr. 1B - H314 Eye Dam. 1 - H318

Specialty Epoxy Resin 1-5%

CAS number: Proprietary

Classification

Acute Tox. 4 - H302

Skin Irrit. 2 - H315

Eye Irrit. 2 - H319

STOT SE 3 - H335

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

EPO-TEK® EK1000-1

Description of first aid measures

Inhalation Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical

attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse

mouth thoroughly with water. Get medical attention if any discomfort continues.

Skin Contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove affected person from source of contamination. Remove any contact lenses and open

eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

Most important symptoms and effects, both acute and delayed

Inhalation Gas or vapor in high concentrations may irritate the respiratory system.

Ingestion May cause discomfort if swallowed.

Skin contact Causes severe burns. May cause sensitisation by skin contact.

Eye contact Causes serious eye damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctorTreat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Dry chemicals. Foam. Carbon dioxide (CO2).

Special hazards arising from the substance or mixture

Hazardous combustion Thermal decomposition

products

Thermal decomposition or combustion products may include the following substances:

Avoid breathing fire gases or vapors. Use water to keep fire exposed containers cool and

Carbon dioxide (CO2). Carbon monoxide (CO).

Advice for firefighters

Protective actions during

disperse vapors.

firefighting

disperse vapor

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Avoid discharge to the aquatic environment.

Methods and material for containment and cleaning up

Methods for cleaning up

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into

containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering

drains, sewers or watercourses.

Reference to other sections For personal protection, see Section 8.

7. Handling and storage

Precautions for safe handling

EPO-TEK® EK1000-1

Usage precautions Avoid spilling. Avoid contact with skin and eyes.

Advice on general occupational hygiene

Provide eyewash station and safety shower. Do not eat, drink or smoke when using this product. Wash after use and before eating, smoking and using the toilet. Wash contaminated

clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions Store at -40°C. Keep container tightly sealed when not in use.

Storage class Chemical storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

Silver

Long-term exposure limit (8-hour TWA): 0.1

Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate general and local exhaust ventilation. Avoid inhalation of vapors.

Eye/face protection Wear tight-fitting, chemical splash goggles or face shield.

Hand protection It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and

before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat,

drink or smoke.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance Paste.

Color Silver.

Odor Mild.

Odor threshold No specific test data are available.

pH No specific test data are available.

Melting point No specific test data are available.

Initial boiling point and range No specific test data are available.

EPO-TEK® EK1000-1

Flash point > 93°C

Evaporation rate < BuAc

Evaporation factor No specific test data are available.

Flammability (solid, gas) No specific test data are available.

Upper/lower flammability or

explosive limits

No specific test data are available.

Vapor pressure No specific test data are available.

Vapor density > 1

Relative density No specific test data are available.

Solubility(ies) No specific test data are available.

Partition coefficient No specific test data are available.

Auto-ignition temperature No specific test data are available.

Decomposition Temperature No specific test data are available.

Viscosity No specific test data are available.

Other information None.

10. Stability and reactivity

Reactivity The following materials may react with the product: Strong acids. Strong alkalis.

Stability Stable at normal ambient temperatures.

Possibility of hazardous

reactions

Will not polymerize.

Conditions to avoid Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of

ignition. Avoid exposure to high temperatures or direct sunlight.

Materials to avoid Strong alkalis. Strong acids.

Hazardous decomposition

products

Thermal decomposition or combustion products may include the following substances:

Carbon monoxide (CO). Carbon dioxide (CO2).

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 15,015.02

Acute toxicity - dermal

ATE dermal (mg/kg) 17,043.15

Acute toxicity - inhalation

ATE inhalation (gases ppm) 69,721.98
ATE inhalation (vapours mg/l) 170.43

23.24

ATE inhalation (dusts/mists

mg/l)

EPO-TEK® EK1000-1

Inhalation Inhalation of dust during cutting, grinding or sanding operations involving this product may

cause irritation of the respiratory tract. Gas or vapor in high concentrations may irritate the

respiratory system.

Ingestion May cause discomfort if swallowed.

Skin Contact Causes severe burns. May cause sensitisation by skin contact.

Eye contact Causes burns. Causes serious eye damage.

12. Ecological information

Ecotoxicity Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Acute aquatic toxicity

Acute toxicity - fish Not available.

Persistence and degradability

Persistence and degradability No data available.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient No specific test data are available.

Mobility in soil

Mobility No data available.

Other adverse effects

Other adverse effects Not known.

13. Disposal considerations

Waste treatment methods

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

14. Transport information

UN Number

UN No. (TDG) 1760 UN No. (IMDG) 1760 UN No. (ICAO) 1760

UN No. (DOT) UN1760

UN proper shipping name

Proper shipping name (TDG) CORROSIVE LIQUID, N.O.S. (CONTAINS Diluent, Silver)

Proper shipping name (IMDG) CORROSIVE LIQUID, N.O.S. (CONTAINS Diluent, Silver, Silver, Silver, Silver)

Proper shipping name (ICAO) CORROSIVE LIQUID, N.O.S. (CONTAINS Diluent, Silver)

Proper shipping name (DOT) CORROSIVE LIQUIDS, N.O.S. (CONTAINS Diluent, Silver)

Transport hazard class(es)

DOT hazard class 8

EPO-TEK® EK1000-1

DOT hazard label 8
TDG class 8
TDG label(s) 8
IMDG Class 8
ICAO class/division 8

Transport labels



DOT transport labels



Packing group

TDG Packing Group

IMDG packing group

II

ICAO packing group

II

DOT packing group

II

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

EmS F-A, S-B

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

Regulatory References Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of Intellectual Property Rights (TRIPS), Section 7, Art. 39.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities None of the ingredients are listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed:

Silver

1,000 lbs (454 Kg)

EPO-TEK® EK1000-1

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed.

SARA 313 Emission Reporting

The following ingredients are listed:

Silver

CAA Accidental Release Prevention

None of the ingredients are listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed:

Silver

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed.

Massachusetts "Right To Know" List

The following ingredients are listed:

Silver

Rhode Island "Right To Know" List

The following ingredients are listed:

Silver

Minnesota "Right To Know" List

The following ingredients are listed:

Silver

New Jersey "Right To Know" List

The following ingredients are listed:

Silver

Pennsylvania "Right To Know" List

The following ingredients are listed:

Silver

Inventories

EU - EINECS/ELINCS

Some of the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

EPO-TEK® EK1000-1

US - TSCA 12(b) Export Notification

None of the ingredients are listed.

Australia - AICS

Some of the ingredients are listed or exempt.

Japan - ENCS

Some of the ingredients are listed or exempt.

Korea - KECI

Some of the ingredients are listed or exempt.

China - IECSC

Some of the ingredients are listed or exempt.

Philippines - PICCS

Some of the ingredients are listed or exempt.

16. Other information

Revision date 4/22/2021

Supersedes date 10/24/2018

Hazard statements in full H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.