



SAFETY DATA SHEET EPO-TEK® T905-1 Black Part A

1. Identification

Product identifier

Product name EPO-TEK® T905-1 Black Part A
Product number T905-1 Black/A

Recommended use of the chemical and restrictions on use

Application Adhesive.
Uses advised against Use only for intended applications.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.
14 Fortune Drive
Billerica, MA 01821
USA
(978) 667-3805
(978) 663-9782
www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone ChemTel: +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified
Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317
Environmental hazards Aquatic Chronic 3 - H412

Label elements

Hazard symbols



Signal word Danger

Hazard statements H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

EPO-TEK® T905-1 Black Part A

Precautionary statements

P261 Avoid breathing vapor/ spray.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 If on skin: Wash with plenty of water.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains Epoxy Resin Blend, Reactive Diluent

Other hazards

Harmful dust may be released during cutting or grinding process.

Hazards not otherwise classified (HNOC) Contains epoxy constituents. May produce an allergic reaction.

3. Composition/information on ingredients

Mixtures

Epoxy Resin Blend	10-30%
CAS number: Proprietary	
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
Reactive Diluent	5-10%
CAS number: Proprietary	
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

Inhalation Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.

Skin Contact Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

EPO-TEK® T905-1 Black Part A

Most important symptoms and effects, both acute and delayed

Inhalation	Vapors may cause headache, fatigue, dizziness and nausea. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.
Ingestion	May cause discomfort if swallowed.
Skin contact	Causes skin irritation. May cause an allergic skin reaction. May cause sensitisation by skin contact.
Eye contact	Causes serious eye damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Dry chemicals. Foam. Carbon dioxide (CO₂).

Special hazards arising from the substance or mixture

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO₂). Carbon monoxide (CO).

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapors.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Avoid release to the environment.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

Reference to other sections For personal protection, see Section 8.

7. Handling and storage

Precautions for safe handling

Usage precautions Handle all packages and containers carefully to minimize spills. Avoid inhalation of vapors and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet.

Advice on general occupational hygiene Provide eyewash station. Do not eat, drink or smoke when using this product. Wash promptly if skin becomes contaminated. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Use appropriate skin cream to prevent drying of skin.

EPO-TEK® T905-1 Black Part A

Conditions for safe storage, including any incompatibilities

Storage precautions	Store at room temperature. Keep container tightly sealed when not in use.
Storage class	Chemical storage.
<u>Specific end uses(s)</u>	
Specific end use(s)	The identified uses for this product are detailed in Section 1.

8. Exposure controls/Personal protection

Ingredient comments No exposure limits known for ingredient(s).

Exposure controls

Protective equipment



Appropriate engineering controls Provide adequate general and local exhaust ventilation.

Eye/face protection Wear tight-fitting, chemical splash goggles or face shield.

Hand protection It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body protection Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Paste.
Color	Black.
Odor	Mild.
Odor threshold	No specific test data are available.
pH	No specific test data are available.
Melting point	No specific test data are available.
Initial boiling point and range	No specific test data are available.
Flash point	204°C
Evaporation rate	<BuAc
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	No specific test data are available.
Vapor pressure	No specific test data are available.

EPO-TEK® T905-1 Black Part A

Vapor density	>1
Relative density	No specific test data are available.
Solubility(ies)	Slightly soluble in water.
Partition coefficient	No specific test data are available.
Auto-ignition temperature	No specific test data are available.
Decomposition Temperature	No specific test data are available.
Viscosity	No specific test data are available.
Other information	None.

10. Stability and reactivity

Reactivity	The following materials may react violently with the product: Strong oxidizing agents. Strong reducing agents.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	Will not polymerize.
Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of ignition.
Materials to avoid	Strong oxidizing agents. Strong reducing agents.
Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO ₂).

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 6,603.86

Acute toxicity - dermal

ATE dermal (mg/kg) 15,056.58

Acute toxicity - inhalation

ATE inhalation (gases ppm) 57,282.18

ATE inhalation (vapours mg/l) 150.57

ATE inhalation (dusts/mists mg/l) 20.91

Inhalation	Gas or vapor in high concentrations may irritate the respiratory system. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.
Ingestion	May cause discomfort if swallowed.
Skin Contact	Causes skin irritation. May cause an allergic skin reaction. May cause sensitisation by skin contact.

EPO-TEK® T905-1 Black Part A

Eye contact Irritating to eyes. May cause severe eye irritation.

12. Ecological information

Ecotoxicity Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Acute aquatic toxicity

Acute toxicity - fish No information available.

Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient No specific test data are available.

Mobility in soil

Mobility The product has poor water-solubility.

Other adverse effects

Other adverse effects Not known.

13. Disposal considerations**Waste treatment methods**

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).

UN Number

UN No. (International) Not applicable.

UN No. (DOT) Not applicable.

UN proper shipping name

Proper shipping name (International) Not applicable.

Proper shipping name (DOT) Not applicable.

Transport hazard class(es)

Transport Labels (International) No transport warning sign required.

DOT transport labels

No transport warning sign required.

Packing group

Packing group (International) Not applicable.

DOT packing group Not applicable.

EPO-TEK® T905-1 Black Part A

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

Not applicable.

DOT reportable quantity Not applicable.

DOT TIH Zone Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Regulatory References Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of Intellectual Property Rights (TRIPS), Section 7, Art. 39.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are required to be listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are required to be listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are required to be listed.

SARA 313 Emission Reporting

None of the ingredients are required to be listed.

CAA Accidental Release Prevention

None of the ingredients are required to be listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are required to be listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are required to be listed.

California Air Toxics "Hot Spots" (A-I)

None of the ingredients are required to be listed.

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are required to be listed.

Massachusetts "Right To Know" List

None of the ingredients are required to be listed.

Rhode Island "Right To Know" List

None of the ingredients are required to be listed.

Minnesota "Right To Know" List

None of the ingredients are required to be listed.

EPO-TEK® T905-1 Black Part A

New Jersey "Right To Know" List

None of the ingredients are required to be listed.

Pennsylvania "Right To Know" List

None of the ingredients are required to be listed.

Inventories

EU - EINECS/ELINCS

Some of the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed.

Australia - AICS

All the ingredients are listed or exempt.

Japan - ENCS

Some of the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

All the ingredients are listed or exempt.

16. Other information

Revision date	12/4/2019
Revision	2
Supersedes date	10/31/2014
Hazard statements in full	<p>H302 Harmful if swallowed.</p> <p>H312 Harmful in contact with skin.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H318 Causes serious eye damage.</p> <p>H319 Causes serious eye irritation.</p> <p>H332 Harmful if inhaled.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.



SAFETY DATA SHEET

EPO-TEK® T905-1 Black Part B

1. Identification

Product identifier

Product name EPO-TEK® T905-1 Black Part B

Product number T905-1 Black/B

Recommended use of the chemical and restrictions on use

Application Adhesive.

Uses advised against Use only for intended applications.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.
14 Fortune Drive
Billerica, MA 01821
USA
(978) 667-3805
(978) 663-9782
www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone ChemTel: +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Resp. Sens. 1 - H334 Skin Sens. 1 - H317 Carc. 2 - H351 Repr. 1A - H360FD

Environmental hazards Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Human health Contains a substance/a group of substances which may impair fertility. Contains a substance/a group of substances which may damage the unborn child. Contains a substance which may be potentially carcinogenic.

Label elements

Hazard symbols



Signal word

Danger

EPO-TEK® T905-1 Black Part B

Hazard statements	<p>H302 Harmful if swallowed.</p> <p>H314 Causes severe skin burns and eye damage.</p> <p>H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H351 Suspected of causing cancer.</p> <p>H360FD May damage fertility. May damage the unborn child.</p> <p>H410 Very toxic to aquatic life with long lasting effects.</p>
Precautionary statements	<p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.</p> <p>P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.</p> <p>P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P342+P311 If experiencing respiratory symptoms: Call a poison center/ doctor.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Contains	Specialty Aromatic Diamine, Cycloaliphatic Diamine, Cyclic Diamine, Cyclic Ethyleneamine

3. Composition/information on ingredients

Mixtures

Cycloaliphatic Diamine 30-60% CAS number: Proprietary
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412
Specialty Aromatic Diamine 30-60% CAS number: Proprietary
Classification Acute Tox. 4 - H302 Carc. 2 - H351 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410
Tertiary Amine 5-10% CAS number: Proprietary
Classification Skin Irrit. 2 - H315

EPO-TEK® T905-1 Black Part B

Cyclic Diamine	1-5%
CAS number: Proprietary	
Classification	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Resp. Sens. 1 - H334	
Skin Sens. 1 - H317	
Repr. 2 - H361fd	
Cyclic Ethyleneamine	<1%
CAS number: Proprietary	
Classification	
Acute Tox. 3 - H311	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
Repr. 1A - H360FD	
Aquatic Chronic 3 - H412	

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures**Description of first aid measures**

Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin Contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

Most important symptoms and effects, both acute and delayed

General information	Contains a substance which may be potentially carcinogenic. Contains a substance/a group of substances which may damage fertility and the unborn child.
Inhalation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Ingestion	Harmful if swallowed. May cause stomach pain or vomiting. May cause chemical burns in mouth, esophagus and stomach. May cause nausea, headache, dizziness and intoxication.
Skin contact	Causes severe burns. May cause an allergic skin reaction. May cause sensitisation by skin contact.
Eye contact	Causes serious eye damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

5. Fire-fighting measures

EPO-TEK® T905-1 Black Part B

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Dry chemicals. Foam. Carbon dioxide (CO₂).

Special hazards arising from the substance or mixture

Hazardous combustion products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapors.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Avoid release to the environment.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

Reference to other sections For personal protection, see Section 8.

7. Handling and storage

Precautions for safe handling

Usage precautions Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Handle all packages and containers carefully to minimize spills. Avoid inhalation of vapors and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet.

Advice on general occupational hygiene Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Eye wash facilities and emergency shower must be available when handling this product. Do not eat, drink or smoke when using this product. Wash promptly if skin becomes contaminated. Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions Store at room temperature. Keep container tightly sealed when not in use.

Storage class Chemical storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

Tertiary Amine

EPO-TEK® T905-1 Black Part B

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

Short-term exposure limit (15-minute): ACGIH

ACGIH = American Conference of Governmental Industrial Hygienists.

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Liquid.
Color	Amber.
Odor	Mild.
Odor threshold	No specific test data are available.
pH	No specific test data are available.
Melting point	No specific test data are available.
Initial boiling point and range	No specific test data are available.
Flash point	> 93°C
Evaporation rate	<BuAc
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	No specific test data are available.
Vapor pressure	No specific test data are available.
Vapor density	>1
Relative density	No specific test data are available.
Solubility(ies)	Soluble in water.
Partition coefficient	No specific test data are available.
Auto-ignition temperature	No specific test data are available.

EPO-TEK® T905-1 Black Part B

Decomposition Temperature No specific test data are available.

Viscosity No specific test data are available.

Other information None.

10. Stability and reactivity

Reactivity The following materials may react violently with the product: Strong oxidizing agents. Strong reducing agents.

Stability Stable at normal ambient temperatures and when used as recommended.

Possibility of hazardous reactions Will not polymerize.

Conditions to avoid Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of ignition.

Materials to avoid Strong oxidizing agents. Strong reducing agents.

Hazardous decomposition products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. Oxides of carbon. Oxides of nitrogen.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 581.4

Acute toxicity - dermal

ATE dermal (mg/kg) 2,366.44

Inhalation May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Ingestion Harmful if swallowed. May cause chemical burns in mouth, esophagus and stomach. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication.

Skin Contact Causes severe burns. May cause an allergic skin reaction. May cause sensitisation by skin contact.

Eye contact Risk of serious damage to eyes. Causes burns.

Acute and chronic health hazards Possible risk of adverse reproductive effects. Known or suspected carcinogen for humans.

Toxicological information on ingredients.

Tertiary Amine

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Reasonably anticipated to be a human carcinogen.

OSHA Carcinogenicity Not listed.

12. Ecological information

EPO-TEK® T905-1 Black Part B

Ecotoxicity	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Toxicity	Very toxic to aquatic organisms.
<u>Persistence and degradability</u>	
Persistence and degradability	No data available.
<u>Bioaccumulative potential</u>	
Bio-Accumulative Potential	No data available on bioaccumulation.
Partition coefficient	No specific test data are available.
<u>Mobility in soil</u>	
Mobility	Semi-mobile.
<u>Other adverse effects</u>	
Other adverse effects	Not known.

13. Disposal considerations**Waste treatment methods**

Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
-------------------------	-----------------------------------------------------------------------------------------------------------------------------

14. Transport information**UN Number**

UN No. (TDG)	2735
UN No. (IMDG)	2735
UN No. (ICAO)	2735
UN No. (DOT)	UN2735

UN proper shipping name

Proper shipping name (TDG)	AMINES, LIQUID, CORROSIVE, N.O.S. (Specialty Aromatic Diamine, Cycloaliphatic Diamine)
Proper shipping name (IMDG)	AMINES, LIQUID, CORROSIVE, N.O.S. (Specialty Aromatic Diamine, Cycloaliphatic Diamine)
Proper shipping name (ICAO)	AMINES, LIQUID, CORROSIVE, N.O.S. (Specialty Aromatic Diamine, Cycloaliphatic Diamine)
Proper shipping name (DOT)	AMINES, LIQUID, CORROSIVE, N.O.S. (Specialty Aromatic Diamine, Cycloaliphatic Diamine)

Transport hazard class(es)

DOT hazard class	8
DOT hazard label	8
TDG class	8
TDG label(s)	8
IMDG Class	8
ICAO class/division	8

EPO-TEK® T905-1 Black Part B

Transport labels



DOT transport labels



Packing group

TDG Packing Group III

IMDG packing group III

ICAO packing group III

DOT packing group III

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

IMDG Code segregation group 18. Alkalis

EmS F-A, S-B

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Regulatory References Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of Intellectual Property Rights (TRIPS), Section 7, Art. 39.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are required to be listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are required to be listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are required to be listed.

SARA 313 Emission Reporting

None of the ingredients are required to be listed.

CAA Accidental Release Prevention

None of the ingredients are required to be listed.

EPO-TEK® T905-1 Black Part B

OSHA Highly Hazardous Chemicals

None of the ingredients are required to be listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are required to be listed.

California Air Toxics "Hot Spots" (A-I)

None of the ingredients are required to be listed.

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are required to be listed.

Massachusetts "Right To Know" List

The following ingredients are listed:

Cyclic Diamine

Cyclic Ethyleneamine

Tertiary Amine

Rhode Island "Right To Know" List

The following ingredients are listed:

Tertiary Amine

Minnesota "Right To Know" List

The following ingredients are listed:

Tertiary Amine

New Jersey "Right To Know" List

The following ingredients are listed:

Cyclic Diamine

Cyclic Ethyleneamine

Tertiary Amine

Cycloaliphatic Diamine

Pennsylvania "Right To Know" List

The following ingredients are listed:

Cyclic Diamine

Cyclic Ethyleneamine

Tertiary Amine

Inventories

EU - EINECS/ELINCS

Some of the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

EPO-TEK® T905-1 Black Part B**US - TSCA 12(b) Export Notification**

None of the ingredients are listed.

Australia - AICS

All the ingredients are listed or exempt.

Japan - ENCS

Some of the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

All the ingredients are listed or exempt.

16. Other information

Revision date	12/4/2019
Revision	2
Supersedes date	10/31/2014
Hazard statements in full	<p>H302 Harmful if swallowed. H311 Toxic in contact with skin. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H351 Suspected of causing cancer. H360FD May damage fertility. May damage the unborn child. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.</p>

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.