

**SECTION 1: Identification****1.1. Identification**

Product form : Mixture  
Product name : TR2139-LH PART A

**1.2. Recommended use and restrictions on use**

Recommended use : Adhesives  
Restrictions on use : Not to be used for any purpose other than the one the product was designed for

**1.3. Supplier**

Epoxy Technology, Inc.  
14 Fortune Drive  
Billerica, MA 01821  
USA  
T 978-667-3805 - F 978-663-9782  
[www.epotek.com](http://www.epotek.com)

**1.4. Emergency telephone number**

Emergency number : VelocityEHS: +1 (800) 255-3924, +1 (813) 248-0585

**SECTION 2: Hazard(s) identification****2.1. Classification of the substance or mixture****GHS US classification**

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Hazardous to the aquatic environment – Chronic Hazard Category 2	H411	Toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

**2.2. GHS Label elements, including precautionary statements****GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS US) : P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 - If on skin: Wash with plenty of water.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.

# TR2139-LH PART A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P363 - Wash contaminated clothing before reuse.

P391 - Collect spillage.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

### 2.4. Unknown acute toxicity (GHS US)

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Epoxy phenol novolac resin	CAS-No.: 9003-36-5	30 – 60	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Titanium oxide (TiO <sub>2</sub> )	CAS-No.: 13463-67-7	< 5	Carc. 2, H351

Comments : Components not listed are either non-hazardous or are below reportable limits.

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs:  
Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

# TR2139-LH PART A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.  
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### TR2139-LH PART A

No additional information available

#### Epoxy phenol novolac resin (9003-36-5)

No additional information available

# TR2139-LH PART A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Titanium oxide (TiO <sub>2</sub> ) (13463-67-7)	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Titanium dioxide (*not respirable as contained in this liquid mixture)
ACGIH OEL TWA	0.2 mg/m <sup>3</sup> (Respirable fraction) 2.5 mg/m <sup>3</sup> (Respirable fraction)
Remark (ACGIH)	TLV® Basis: LRT irr; pneumoconiosis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2022
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Titanium dioxide (*not respirable as contained in this liquid mixture)

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

<b>Hand protection:</b>
Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear
<b>Eye protection:</b>
Safety glasses
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Color : Cream  
Odor : Mild odour  
Odor threshold : No data available  
pH : No data available  
Melting point : No data available  
Freezing point : No data available  
Boiling point : No data available  
Flash point : No data available  
Relative evaporation rate (butyl acetate=1) : No data available

# TR2139-LH PART A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Titanium oxide (TiO <sub>2</sub> ) (13463-67-7)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 oral	5000 mg/kg
LC50 Inhalation - Rat	> 5.09 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))

# TR2139-LH PART A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Titanium oxide (TiO <sub>2</sub> ) (13463-67-7)	
LC50 Inhalation - Rat (Dust/Mist)	> 3.43 mg/l Source: ECHA
ATE US (oral)	5000 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
Epoxy phenol novolac resin (9003-36-5)	
pH	No data available in the literature
Titanium oxide (TiO <sub>2</sub> ) (13463-67-7)	
pH	7 (aqueous suspension, 10 %)
Serious eye damage/irritation	: Not classified
Epoxy phenol novolac resin (9003-36-5)	
pH	No data available in the literature
Titanium oxide (TiO <sub>2</sub> ) (13463-67-7)	
pH	7 (aqueous suspension, 10 %)
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.
Titanium oxide (TiO <sub>2</sub> ) (13463-67-7)	
Additional information	*Not a respirable hazard as contained in this liquid mixture
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Epoxy phenol novolac resin (9003-36-5)	
NOAEL (oral,rat,90 days)	≈ 250 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Epoxy phenol novolac resin (9003-36-5)	
Viscosity, kinematic	No data available in the literature
Titanium oxide (TiO <sub>2</sub> ) (13463-67-7)	
Viscosity, kinematic	Not applicable (solid)
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Epoxy phenol novolac resin (9003-36-5)	
LC50 - Fish [1]	1.9 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Semi-static system, Fresh water, Weight of evidence)
EC50 - Crustacea [1]	3.5 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Weight of evidence, GLP)

# TR2139-LH PART A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Epoxy phenol novolac resin (9003-36-5)	
LC50 - Fish [2]	1000 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 72h - Algae [1]	1.8 mg/l (Equivalent or similar to OECD 201, Selenastrum capricornutum, Static system, Fresh water, Experimental value)
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Titanium oxide (TiO <sub>2</sub> ) (13463-67-7)	
LC50 - Fish [1]	> 1000 mg/l (Pisces, Fresh water)
EC50 - Crustacea [1]	> 1000 mg/l (Invertebrata, Fresh water)
EC50 72h - Algae [1]	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)

### 12.2. Persistence and degradability

Epoxy phenol novolac resin (9003-36-5)	
Not rapidly degradable	
Persistence and degradability	Not readily biodegradable in water.
Titanium oxide (TiO <sub>2</sub> ) (13463-67-7)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

### 12.3. Bioaccumulative potential

Epoxy phenol novolac resin (9003-36-5)	
Partition coefficient n-octanol/water (Log Pow)	2.7 – 3.6 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Titanium oxide (TiO <sub>2</sub> ) (13463-67-7)	
Bioaccumulative potential	Not bioaccumulative.

### 12.4. Mobility in soil

Epoxy phenol novolac resin (9003-36-5)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.65 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.
Titanium oxide (TiO <sub>2</sub> ) (13463-67-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.

### 12.5. Other adverse effects

No additional information available

# TR2139-LH PART A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations





### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
<b>14.1. UN number</b>			
3082	UN3082	3082	3082
<b>14.2. Proper Shipping Name</b>			
Environmentally hazardous substances, liquid, n.o.s. (Epoxy Phenol Novolac)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Phenol Novolac)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Phenol Novolac)	Environmentally hazardous substance, liquid, n.o.s. (Epoxy Phenol Novolac)
<b>14.3. Transport hazard class(es)</b>			
9	9	9	9
			
<b>14.4. Packing group</b>			
III	III	III	III
<b>14.5. Environmental hazards</b>			
Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
No supplementary information available			

#### 14.6. Special precautions for user

##### DOT

UN-No.(DOT) : UN3082



# TR2139-LH PART A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

DOT Special Provisions (49 CFR 172.102)	: 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies. 146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination. 173 - An appropriate generic entry may be used for this material. 335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s.," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 155
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: No Limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: No Limit
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
<b>TDG</b>	
UN-No. (TDG)	: UN3082

# TR2139-LH PART A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS,99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, may be offered for transport, handled or transported as UN3077 if there is no visible liquid when the dangerous goods are loaded into a means of containment and during transport. (2) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no release of the dangerous goods that could endanger public safety.
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Emergency Response Guide (ERG) Number	: 171
<b>IMDG</b>	
Special provision (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
Stowage category (IMDG)	: A
<b>IATA</b>	
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provision (IATA)	: A97, A158, A197, A215

# TR2139-LH PART A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ERG code (IATA) : 9L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Aluminum oxide (Al <sub>2</sub> O <sub>3</sub> ) (non-fibrous)	CAS-No. 1344-28-1	10 – 60%
--	-------------------	----------

### 15.2. International regulations

#### CANADA

#### Epoxy phenol novolac resin (9003-36-5)

Listed on the Canadian DSL (Domestic Substances List)

#### Titanium oxide (TiO<sub>2</sub>) (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

#### Epoxy phenol novolac resin (9003-36-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Titanium oxide (TiO<sub>2</sub>) (13463-67-7)

Listed on IARC (International Agency for Research on Cancer)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Titanium oxide (TiO <sub>2</sub> )(13463-67-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 9/26/2023

# TR2139-LH PART A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

Full text of H-phrases	
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H351	Suspected of causing cancer
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

**SECTION 1: Identification**

**1.1. Identification**

Product form : Mixture  
Product name : TR2139-LH PART B

**1.2. Recommended use and restrictions on use**

Recommended use : Adhesives  
Restrictions on use : Not to be used for any purpose other than the one the product was designed for

**1.3. Supplier**

Epoxy Technology, Inc.  
14 Fortune Drive  
Billerica, MA 01821  
USA  
T 978-667-3805 - F 978-663-9782  
[www.epotek.com](http://www.epotek.com)

**1.4. Emergency telephone number**

Emergency number : VelocityEHS: +1 (800) 255-3924, +1 (813) 248-0585

**SECTION 2: Hazard(s) identification**

**2.1. Classification of the substance or mixture**

**GHS US classification**

Acute toxicity (oral) Category 3	H301	Toxic if swallowed
Acute toxicity (inhalation:dust,mist) Category 4	H332	Harmful if inhaled
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Reproductive toxicity Category 1B	H360	May damage fertility or the unborn child
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation

Full text of H statements : see section 16

**2.2. GHS Label elements, including precautionary statements**

**GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H301 - Toxic if swallowed  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H332 - Harmful if inhaled  
H335 - May cause respiratory irritation  
H360 - May damage fertility or the unborn child

# TR2139-LH PART B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 - If swallowed: Immediately call a poison center or doctor.  
P302+P352 - If on skin: Wash with plenty of water.  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P310 - Immediately call a poison center or doctor.  
P312 - Call a poison center or doctor if you feel unwell.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P330 - Rinse mouth.  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P363 - Wash contaminated clothing before reuse.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

### 2.4. Unknown acute toxicity (GHS US)

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Substituted imidazole	CAS-No.: 23996-25-0	≥ 60	Acute Tox. 3 (Oral), H301 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Diethylenetriamine	CAS-No.: 111-40-0	< 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335

# TR2139-LH PART B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Phenol, 4,4'-(1-methylethylidene)bis-	CAS-No.: 80-05-7	< 0.20	Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 1B, H360 STOT SE 3, H335 Aquatic Chronic 2, H411

Comments : Components not listed are either non-hazardous or are below reportable limits.  
Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.  
First-aid measures after ingestion : Rinse mouth. Call a physician immediately.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause respiratory irritation.  
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Serious damage to eyes.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing dust/fume/gas/mist/vapors/spray.

# TR2139-LH PART B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### TR2139-LH PART B

No additional information available

#### Phenol, 4,4'-(1-methylethylidene)bis- (80-05-7)

No additional information available

#### Diethylenetriamine (111-40-0)

##### USA - ACGIH - Occupational Exposure Limits

Local name	Diethylenetriamine
ACGIH OEL TWA [ppm]	1 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr. Notations: Skin
Regulatory reference	ACGIH 2022

#### Substituted imidazole (23996-25-0)

No additional information available



# TR2139-LH PART B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Amber
Odor	: Mild odour
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

# TR2139-LH PART B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Toxic if swallowed.  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Harmful if inhaled.

TR2139-LH PART B	
ATE US (oral)	144.098 mg/kg body weight
ATE US (dust, mist)	4.762 mg/l/4h
Phenol, 4,4'-(1-methylethylidene)bis- (80-05-7)	
LD50 oral rat	2000 – 5000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 oral	3300 mg/kg
LD50 dermal rabbit	3000 mg/kg body weight (Rabbit, Experimental value, Dermal)
LD50 dermal	3000 mg/kg
ATE US (oral)	2000 mg/kg body weight
ATE US (dermal)	3000 mg/kg body weight
Diethylenetriamine (111-40-0)	
LD50 oral rat	1553 mg/kg body weight (Rat, Male, Experimental value, Oral, 14 day(s))
LD50 oral	1080 mg/kg
LD50 dermal rabbit	1045 mg/kg body weight (Rabbit, Experimental value, Dermal)

# TR2139-LH PART B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Diethylenetriamine (111-40-0)</b>	
LD50 dermal	1040 mg/kg
ATE US (oral)	1080 mg/kg body weight
ATE US (dermal)	1040 mg/kg body weight
ATE US (gases)	100 ppmV/4h
ATE US (vapors)	0.5 mg/l/4h
ATE US (dust, mist)	0.05 mg/l/4h
<b>Substituted imidazole (23996-25-0)</b>	
ATE US (oral)	100 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
<b>Phenol, 4,4'-(1-methylethylidene)bis- (80-05-7)</b>	
pH	No data available in the literature
Serious eye damage/irritation	: Causes serious eye damage.
<b>Phenol, 4,4'-(1-methylethylidene)bis- (80-05-7)</b>	
pH	No data available in the literature
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: May damage fertility or the unborn child.
STOT-single exposure	: May cause respiratory irritation.
<b>Phenol, 4,4'-(1-methylethylidene)bis- (80-05-7)</b>	
STOT-single exposure	May cause respiratory irritation.
<b>Diethylenetriamine (111-40-0)</b>	
STOT-single exposure	May cause respiratory irritation.
<b>Substituted imidazole (23996-25-0)</b>	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
<b>Phenol, 4,4'-(1-methylethylidene)bis- (80-05-7)</b>	
LOAEL (oral,rat,90 days)	600 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
<b>Diethylenetriamine (111-40-0)</b>	
LOAEL (oral,rat,90 days)	530 – 620 mg/kg body weight Animal: rat, Guideline: other:OECD Guideline for Testing of Chemicals, No. 451, May 12, 1981
NOAEL (oral,rat,90 days)	70 – 80 mg/kg body weight Animal: rat, Guideline: other:OECD Guideline for Testing of Chemicals, No. 451, May 12, 1981
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
<b>Phenol, 4,4'-(1-methylethylidene)bis- (80-05-7)</b>	
Viscosity, kinematic	Not applicable (solid)
<b>Diethylenetriamine (111-40-0)</b>	
Viscosity, kinematic	5.268 mm <sup>2</sup> /s

# TR2139-LH PART B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

<b>Phenol, 4,4'-(1-methylethylidene)bis- (80-05-7)</b>	
LC50 - Fish [1]	4.6 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	10.2 mg/l (ASTM E-35.21, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Lethal)
EC50 96h - Algae [1]	2.73 – 3.1 mg/l (EPA 600/9-78-018, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
EC50 96h - Algae [2]	1.4 mg/l Test organisms (species): Skeletonema costatum
LOEC (chronic)	3.6 mg/l Test organisms (species): other:Rotifer (Brachionus calyciflorus) Duration: '48 h'
NOEC chronic fish	0.16 mg/l

<b>Diethylenetriamine (111-40-0)</b>	
LC50 - Fish [1]	430 mg/l (EU Method C.1, 96 h, Poecilia reticulata, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	64.6 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [2]	16 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	187 mg/l Source: ECHA
ErC50 algae	1164 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Selenastrum capricornutum, Static system, Fresh water, Experimental value, GLP)
LOEC (chronic)	11.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	5.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 10 mg/l Test organisms (species): Gasterosteus aculeatus Duration: '28 d'
NOEC chronic crustacea	5.6 mg/l

#### 12.2. Persistence and degradability

<b>Phenol, 4,4'-(1-methylethylidene)bis- (80-05-7)</b>	
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.
Chemical oxygen demand (COD)	0.036 g O <sub>2</sub> /g substance
ThOD	2.5 g O <sub>2</sub> /g substance

<b>Diethylenetriamine (111-40-0)</b>	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.

# TR2139-LH PART B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Substituted imidazole (23996-25-0)

Not rapidly degradable

### 12.3. Bioaccumulative potential

#### Phenol, 4,4'-(1-methylethylidene)bis- (80-05-7)

BCF - Fish [1]	5.1 – 67 (42 day(s), Cyprinus carpio, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	3.4 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 21.5 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

#### Diethylenetriamine (111-40-0)

BCF - Fish [1]	0.3 – 6.3 (OECD 305: Bioconcentration: Flow-Through Fish Test, 8 week(s), Cyprinus carpio, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	-1.58 (Calculated, 20 °C)
Bioaccumulative potential	Not bioaccumulative.

### 12.4. Mobility in soil

#### Phenol, 4,4'-(1-methylethylidene)bis- (80-05-7)

Surface tension	No data available (test not performed)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.8 – 2.97 (log Koc, OECD 106: Adsorption/Desorption Using a Batch Equilibrium Method, Experimental value, GLP)
Ecology - soil	Low potential for adsorption in soil.

#### Diethylenetriamine (111-40-0)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.4 – 4.6 (log Koc, Other, Experimental value, GLP)
Ecology - soil	Adsorbs into the soil. Low potential for mobility in soil. Soil contaminant.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information





In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
<b>14.1. UN number</b>			
2810	UN2810	2810	2810

# TR2139-LH PART B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	TDG	IMDG	IATA
<b>14.2. Proper Shipping Name</b>			
Toxic, liquids, organic, n.o.s. (Substituted imidazole)	TOXIC LIQUID, ORGANIC, N.O.S. (Substituted imidazole)	TOXIC LIQUID, ORGANIC, N.O.S. (Substituted imidazole)	Toxic liquid, organic, n.o.s. (Substituted imidazole)
<b>14.3. Transport hazard class(es)</b>			
6.1	6.1	6.1	6.1
			
<b>14.4. Packing group</b>			
III	III	III	III
<b>14.5. Environmental hazards</b>			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

### 14.6. Special precautions for user

#### DOT

- UN-No.(DOT) : UN2810
- DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 153
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
- DOT Packaging Bulk (49 CFR 173.xxx) : 241
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L
- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
- DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

#### TDG

- UN-No. (TDG) : UN2810

# TR2139-LH PART B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS.
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 60 L
Emergency Response Guide (ERG) Number	: 153

### IMDG

Special provision (IMDG)	: 223, 274
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP28
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-A - SPILLAGE SCHEDULE Alfa - TOXIC SUBSTANCES
Stowage category (IMDG)	: A
Stowage and handling (IMDG)	: SW2
Properties and observations (IMDG)	: Toxic if swallowed, by skin contact or by inhalation.

### IATA

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y642
PCA limited quantity max net quantity (IATA)	: 2L
PCA packing instructions (IATA)	: 655
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 663
CAO max net quantity (IATA)	: 220L
Special provision (IATA)	: A3, A4, A137
ERG code (IATA)	: 6L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# TR2139-LH PART B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

#### 15.2. International regulations

##### CANADA

##### Phenol, 4,4'-(1-methylethylidene)bis- (80-05-7)

Listed on the Canadian DSL (Domestic Substances List)

##### Diethylenetriamine (111-40-0)

Listed on the Canadian DSL (Domestic Substances List)

##### Substituted imidazole (23996-25-0)

Listed on the Canadian DSL (Domestic Substances List)

##### EU-Regulations

No additional information available

##### National regulations


##### Phenol, 4,4'-(1-methylethylidene)bis- (80-05-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

##### Diethylenetriamine (111-40-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### 15.3. US State regulations

 **WARNING:** This product can expose you to Bisphenol A (BPA), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Component	State or local regulations
Phenol, 4,4'-(1-methylethylidene)bis-(80-05-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Diethylenetriamine(111-40-0)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 9/15/2023

#### Full text of H-phrases

H301	Toxic if swallowed
H302	Harmful if swallowed



# TR2139-LH PART B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H330	Fatal if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H360	May damage fertility or the unborn child
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.