



SAFETY DATA SHEET

EPO-TEK® 360T PMF Syringe

1. Identification

Product identifier

Product name EPO-TEK® 360T PMF Syringe
Product number 360T

Recommended use of the chemical and restrictions on use

Application Adhesive.
Uses advised against Use only for intended applications. Restricted to professional users.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.
 14 Fortune Drive
 Billerica, MA 01821
 USA
 (978) 667-3805
 (978) 663-9782
 www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone ChemTel: +1 (800) 255-3924, +1 (813) 248-0585


2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified
Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Repr. 1B - H360 STOT SE 1 - H370
Environmental hazards Aquatic Chronic 2 - H411

Label elements

Pictogram



Signal word

Danger

Hazard statements

H302+H332 Harmful if swallowed or if inhaled.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H360 May damage fertility or the unborn child.
 H370 Causes damage to organs .
 H411 Toxic to aquatic life with long lasting effects.

EPO-TEK® 360T PMF Syringe

Precautionary statements	<p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P301+P312 If swallowed: Call a poison center/ doctor if you feel unwell.</p> <p>P302+P352 If on skin: Wash with plenty of water.</p> <p>P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Supplemental label information	Restricted to professional users.
Contains	Bisphenol A Diglycidyl Ether Resin, Reactive Diluent, Substituted Imidazole, Polar Activator, Imidazole

3. Composition/information on ingredients

Substances

Bisphenol A Diglycidyl Ether Resin	30-60%
CAS number: 25085-99-8	
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
Reactive Diluent	10-30%
CAS number: Proprietary	
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
Substituted Imidazole	5-10%
CAS number: Proprietary	
Classification	
Acute Tox. 4 - H302	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	

EPO-TEK® 360T PMF Syringe

Polar Activator	1-5%
CAS number: Proprietary	
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 3 - H301	
Acute Tox. 3 - H311	
Acute Tox. 3 - H331	
STOT SE 1 - H370	
Imidazole	1-5%
CAS number: 288-32-4	
Classification	
Acute Tox. 4 - H302	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Repr. 1B - H360	

The full text for all hazard statements is displayed in Section 16.

Product name EPO-TEK® 360T PMF Syringe

4. First-aid measures

Description of first aid measures

Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin Contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

Most important symptoms and effects, both acute and delayed

General information	May damage fertility or the unborn child. Causes damage to organs (Eyes, Skin, Respiratory system, lungs, Central nervous system, Gastro-intestinal tract).
Inhalation	Harmful if inhaled. Vapors may cause headache, fatigue, dizziness and nausea. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.
Ingestion	Harmful if swallowed. May cause chemical burns in mouth, esophagus and stomach. May cause stomach pain or vomiting.
Skin contact	Causes skin irritation. Allergic rash. May cause sensitisation by skin contact.
Eye contact	Causes serious eye damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

5. Fire-fighting measures

EPO-TEK® 360T PMF Syringe

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Dry chemicals. Foam. Water spray.

Special hazards arising from the substance or mixture

Hazardous combustion products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapors.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Avoid release to the environment.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

Reference to other sections For personal protection, see Section 8.

7. Handling and storage

Precautions for safe handling

Usage precautions Restricted to professional users. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Handle all packages and containers carefully to minimize spills. Avoid inhalation of vapors and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Wash promptly with soap and water if skin becomes contaminated. Wash contaminated clothing before reuse. Use appropriate skin cream to prevent drying of skin.

Conditions for safe storage, including any incompatibilities

Storage precautions Store at -40°C. Keep container tightly sealed when not in use.

Storage class Chemical storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Polar Activator

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm

Short-term exposure limit (15-minute): ACGIH 250 ppm

EPO-TEK® 360T PMF Syringe

ACGIH = American Conference of Governmental Industrial Hygienists.

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Paste.
Color	Tan.
Odor	Mild.
Odor threshold	No specific test data are available.
pH	No specific test data are available.
Melting point	No specific test data are available.
Initial boiling point and range	No specific test data are available.
Flash point	> 93°C
Evaporation rate	<BuAc
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	No specific test data are available.
Vapor density	>1
Relative density	No specific test data are available.
Solubility(ies)	No specific test data are available.
Partition coefficient	No specific test data are available.
Auto-ignition temperature	No specific test data are available.
Decomposition Temperature	No specific test data are available.
Viscosity	No specific test data are available.
Other information	None.

EPO-TEK® 360T PMF Syringe

10. Stability and reactivity

Reactivity	The following materials may react violently with the product: Strong oxidizing agents. Strong reducing agents.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	May polymerize.
Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of ignition.
Materials to avoid	Strong oxidizing agents. Strong reducing agents.
Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO ₂). Oxides of nitrogen.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 1,021.56

Acute toxicity - dermal

ATE dermal (mg/kg) 3,082.74

Acute toxicity - inhalation

ATE inhalation (gases ppm) 9,958.93

ATE inhalation (vapours mg/l) 30.83

ATE inhalation (dusts/mists mg/l) 4.49

Inhalation	Harmful if inhaled. Vapors may cause headache, fatigue, dizziness and nausea. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.
Ingestion	Harmful if swallowed. May cause chemical burns in mouth, esophagus and stomach. May cause stomach pain or vomiting.
Skin Contact	May cause sensitisation by skin contact. Causes skin irritation.
Eye contact	Causes serious eye damage.
Acute and chronic health hazards	Causes damage to organs (Eyes, Skin, Respiratory system, lungs, Gastro-intestinal tract, Central nervous system). May damage fertility or the unborn child.

12. Ecological Information

Ecotoxicity	The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
<u>Acute aquatic toxicity</u>	
Acute toxicity - fish	Not known.
<u>Persistence and degradability</u>	

EPO-TEK® 360T PMF Syringe

Persistence and degradability No data available.

Bioaccumulative potential

Bio-Accumulative Potential No specific test data are available.

Partition coefficient No specific test data are available.

Mobility in soil

Mobility No data available.

Other adverse effects

Other adverse effects Not known.

13. Disposal considerations

Waste treatment methods

General information Dangerous for the environment. May cause long-term adverse effects in the aquatic environment.

14. Transport information

UN Number

UN No. (TDG) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

UN No. (DOT) UN3082

UN proper shipping name

Proper shipping name (TDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Resin)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Resin)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Resin)

Proper shipping name (DOT) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Resin)

Transport hazard class(es)

DOT hazard class 9

DOT hazard label 9

TDG class 9

TDG label(s) 9

IMDG Class 9

ICAO class/division 9

Transport labels



EPO-TEK® 360T PMF Syringe

DOT transport labels



Packing group

TDG Packing Group	III
IMDG packing group	III
ICAO packing group	III
DOT packing group	III

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

EmS F-A, S-F

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Regulatory References Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of Intellectual Property Rights (TRIPS), Section 7, Art. 39.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are required to be listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed or exempt:

Polar Activator

5,000 lbs (2270 Kg)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are required to be listed.

SARA 313 Emission Reporting

The following ingredients are listed or exempt:

Polar Activator

CAA Accidental Release Prevention

None of the ingredients are required to be listed.

SARA (311/312) Hazard Categories

None of the ingredients are required to be listed.

EPO-TEK® 360T PMF Syringe

OSHA Highly Hazardous Chemicals

None of the ingredients are required to be listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

WARNING: This product contains a substance known to the State of California to cause cancer and/or reproductive harm.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

Polar Activator

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are required to be listed.

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

Polar Activator

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

Polar Activator

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

Polar Activator

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

Polar Activator

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

Polar Activator

Inventories

EU - EINECS/ELINCS

Some of the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

Australia - AICS

All the ingredients are listed or exempt.

Japan - MITI

Some of the ingredients are listed or exempt.

EPO-TEK® 360T PMF Syringe

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

All the ingredients are listed or exempt.

16. Other information

Revision date	5/22/2018
Revision	1
Hazard statements in full	H225 Highly flammable liquid and vapor. H301 Toxic if swallowed. H302 Harmful if swallowed. H311 Toxic in contact with skin. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H360 May damage fertility or the unborn child. H370 Causes damage to organs . H411 Toxic to aquatic life with long lasting effects.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.