

SAFETY DATA SHEET EPO-TEK® 730 PMF Syringe

1. Identification

Product identifier

Product name EPO-TEK® 730 PMF Syringe

Product number 730

Recommended use of the chemical and restrictions on use

Application Adhesive.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.

14 Fortune Drive Billerica, MA 01821

USA

(978) 667-3805 (978) 663-9782

www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 1 -

H370

Environmental hazards Aquatic Chronic 3 - H412

Label elements

Pictogram







Signal word

Danger

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H370 Causes damage to organs.

H412 Harmful to aquatic life with long lasting effects.

EPO-TEK® 730 PMF Syringe

Precautionary statements P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P501 Dispose of contents/ container in accordance with national regulations.

Contains Epoxy Resin Blend, Reactive Diluent Blend, Polar Activator, Curing Agent

Other hazards

Hazards not otherwise classified (HNOC)

Contains epoxy constituents. May produce an allergic reaction.

3. Composition/information on ingredients

Mixtures

Epoxy Resin Blend
CAS number: Proprietary

Classification
Skin Irrit. 2 - H315

Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

Reactive Diluent Blend

CAS number: Proprietary

Classification

Acute Tox. 4 - H302

Acute Tox. 4 - H312

Acute Tox. 4 - H332

Skin Irrit. 2 - H315

Polar Activator

CAS number: Proprietary

Classification
Flam. Liq. 2 - H225

Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370

Eye Dam. 1 - H318 Skin Sens. 1 - H317

EPO-TEK® 730 PMF Syringe

Curing Agent 1-5%

CAS number: Proprietary

Classification

Acute Tox. 4 - H312 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

General information Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air at once. Keep affected person warm and at rest. Get

medical attention immediately.

Ingestion Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention

immediately.

Skin Contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort

continues.

Most important symptoms and effects, both acute and delayed

General information Causes damage to organs.

Inhalation Harmful if inhaled. May cause respiratory irritation.

Ingestion May cause discomfort if swallowed.

Skin contact Causes skin irritation. May cause sensitisation by skin contact.

Eye contact Causes serious eye damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctorTreat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Water spray, fog or mist. Foam. Powder.

Special hazards arising from the substance or mixture

Hazardous combustion

Thermal decomposition or combustion products may include the following substances:

Carbon monoxide (CO). Carbon dioxide (CO2).

Advice for firefighters

Protective actions during

Avoid breathing fire gases or vapors. Use water to keep fire exposed containers cool and

disperse vapors.

Special protective equipment

for firefighters

products

firefighting

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

EPO-TEK® 730 PMF Syringe

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Avoid release to the environment.

Methods and material for containment and cleaning up

Methods for cleaning up Provide adequate ventilation. Wear suitable protective equipment, including gloves,

goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb in vermiculite,

dry sand or earth and place into containers.

Reference to other sections For personal protection, see Section 8.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation

of vapors. Use approved respirator if air contamination is above an acceptable level. Persons

susceptible to allergic reactions should not handle this product.

Advice on general occupational hygiene

Provide eyewash station. Do not eat, drink or smoke when using this product. Wash after use and before eating, smoking and using the toilet. Wash contaminated clothing before reuse.

Use appropriate skin cream to prevent drying of skin.

Conditions for safe storage, including any incompatibilities

Storage precautions Store at -40°C. Keep container tightly sealed when not in use.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Polar Activator

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm Short-term exposure limit (15-minute): ACGIH 250 ppm

ACGIH = American Conference of Governmental Industrial Hygienists.

Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate general and local exhaust ventilation.

Eye/face protection Wear tight-fitting, chemical splash goggles or face shield.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapor contact.

EPO-TEK® 730 PMF Syringe

Hygiene measures Do not smoke in work area. Wash at the end of each work shift and before eating, smoking

> and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or

smoke.

> 93°C

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Paste. **Appearance**

Color Tan. Odor Mild.

Flash point **Evaporation rate** <BuAc

Vapor density >1

Solubility(ies) Slightly soluble in water.

Other information None.

10. Stability and reactivity

Reactivity The following materials may react with the product: Strong oxidizing agents. Strong reducing

Stability Stable at normal ambient temperatures and when used as recommended.

Possibility of hazardous

reactions

May polymerize.

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods

of time.

Materials to avoid Strong oxidizing agents. Strong acids. Strong alkalis.

Hazardous decomposition

products

Heating may generate the following products: Toxic gases/vapors/fumes of: Carbon dioxide

(CO2). Carbon monoxide (CO).

11. Toxicological information

Information on toxicological effects

General information Causes damage to organs.

Inhalation Harmful if inhaled. May cause respiratory system irritation.

EPO-TEK® 730 PMF Syringe

Ingestion May cause discomfort if swallowed.

Skin ContactCauses skin irritation. May cause sensitisation by skin contact.

Eye contact Causes serious eye damage.

12. Ecological Information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Acute toxicity - fish Not available.

Persistence and degradability

Persistence and degradability No data available.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Mobility in soil

Mobility The product has poor water-solubility.

Other adverse effects

Other adverse effects Not known.

13. Disposal considerations

Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

14. Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, DOT).

UN Number

Not applicable.

UN proper shipping name

Not applicable.

Transport hazard class(es)

No transport warning sign required.

Transport labels

No transport warning sign required.

DOT transport labels

No transport warning sign required.

Packing group

Not applicable.

EPO-TEK® 730 PMF Syringe

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

Not applicable.

DOT TIH Zone Not applicable.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

Regulatory References Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of

Intellectual Property Rights (TRIPS), Section 7, Art. 39.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are required to be listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed or exempt:

Polar Activator

5,000 lbs (2270 Kg)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are required to be listed.

SARA 313 Emission Reporting

The following ingredients are listed or exempt:

Polar Activator

CAA Accidental Release Prevention

None of the ingredients are required to be listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are required to be listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

WARNING: This product contains a substance known to the State of California to cause cancer and/or reproductive harm.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

Polar Activator

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are required to be listed.

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

Polar Activator

EPO-TEK® 730 PMF Syringe

Curing Agent

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

Polar Activator

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

Polar Activator

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

Polar Activator

Curing Agent

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

Polar Activator

Curing Agent

Inventories

EU - EINECS/ELINCS

Some of the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

Australia - AICS

All the ingredients are listed or exempt.

Japan - MITI

Some of the ingredients are listed or exempt.

Korea - KECI

Some of the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

Some of the ingredients are listed or exempt.

16. Other information

Revision date 9/13/2017

Revision

EPO-TEK® 730 PMF Syringe

Hazard statements in full H225 Highly flammable liquid and vapor.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H370 Causes damage to organs.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.