

# SAFETY DATA SHEET EPO-TEK® E4110 PMF Syringe

#### 1. Identification

**Product identifier** 

Product name EPO-TEK® E4110 PMF Syringe

Product number E4110

Recommended use of the chemical and restrictions on use

**Application** Adhesive.

Uses advised against

Use only for intended applications.

Details of the supplier of the safety data sheet

**Supplier** Epoxy Technology, Inc.

14 Fortune Drive Billerica, MA 01821

USA

(978) 667-3805 (978) 663-9782

www.epotek.com, SDS@epotek.com

**Emergency telephone number** 

Emergency telephone ChemTel: +1 (800) 255-3924, +1 (813) 248-0585

# 2. Hazard(s) identification

# Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317

**Environmental hazards** Aquatic Chronic 2 - H411

Label elements

Hazard symbols







Signal word Danger

**Hazard statements** H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

# **EPO-TEK® E4110 PMF Syringe**

**Precautionary statements** P280 Wear protective gloves/ protective clothing/ eye protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/ shower.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/ container in accordance with national regulations.

Contains Epoxy Phenol Novolac, Polyoxypropylenediamine, Reactive Diluent, Reactive Diluent

Other hazards

Hazards not otherwise classified (HNOC)

Contains epoxy constituents. May produce an allergic reaction.

# 3. Composition/information on ingredients

#### **Mixtures**

Silver 60-100%

CAS number: 7440-22-4

Classification

Aquatic Chronic 2 - H411

# Epoxy Phenol Novolac 10-30%

CAS number: 9003-36-5

#### Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

# Polyoxypropylenediamine 5-10%

CAS number: 9046-10-0

# Classification

Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318

#### Reactive Diluent 1-5%

CAS number: Proprietary

#### Classification

Acute Tox. 4 - H302

Acute Tox. 4 - H312

Acute Tox. 4 - H332

Skin Irrit. 2 - H315

Eye Dam. 1 - H318

Skin Sens. 1 - H317

# **EPO-TEK® E4110 PMF Syringe**

Reactive Diluent 1-5%

CAS number: Proprietary

Classification

Acute Tox. 4 - H302 Eye Dam. 1 - H318 STOT SE 3 - H336

The full text for all hazard statements is displayed in Section 16.

#### 4. First-aid measures

#### Description of first aid measures

**Inhalation** Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical

attention if any discomfort continues.

**Ingestion** Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse

mouth thoroughly with water. Get medical attention if any discomfort continues.

**Skin Contact** Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

**Eye contact** Remove affected person from source of contamination. Remove any contact lenses and open

eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

#### Most important symptoms and effects, both acute and delayed

**Inhalation** Gas or vapor in high concentrations may irritate the respiratory system.

**Ingestion** May cause discomfort if swallowed.

**Skin contact** Causes severe burns. May cause sensitisation by skin contact.

**Eye contact** Causes serious eye damage.

# Indication of immediate medical attention and special treatment needed

#### 5. Fire-fighting measures

# Extinguishing media

Suitable extinguishing media Dry chemicals. Foam. Carbon dioxide (CO2).

## Special hazards arising from the substance or mixture

Hazardous combustion

Thermal decomposition or combustion products may include the following substances:

Carbon dioxide (CO2). Carbon monoxide (CO).

Advice for firefighters

products

firefighting

Protective actions during

Avoid breathing fire gases or vapors. Use water to keep fire exposed containers cool and

disperse vapors.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

# 6. Accidental release measures

# Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet.

#### **Environmental precautions**

# **EPO-TEK® E4110 PMF Syringe**

**Environmental precautions** Avoid discharge to the aquatic environment.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into

containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering

drains, sewers or watercourses.

**Reference to other sections** For personal protection, see Section 8.

# 7. Handling and storage

#### Precautions for safe handling

**Usage precautions** Avoid spilling. Avoid contact with skin and eyes.

Advice on general occupational hygiene

Provide eyewash station and safety shower. Do not eat, drink or smoke when using this product. Wash after use and before eating, smoking and using the toilet. Wash contaminated

clothing before reuse.

#### Conditions for safe storage, including any incompatibilities

**Storage precautions** Store at -40°C. Keep container tightly sealed when not in use.

Storage class Chemical storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

#### 8. Exposure controls/Personal protection

# **Control parameters**

## Occupational exposure limits

Silver

Long-term exposure limit (8-hour TWA): 0.1

# **Exposure controls**

#### Protective equipment





Appropriate engineering

controls

Provide adequate general and local exhaust ventilation. Avoid inhalation of vapors.

**Eye/face protection** Wear tight-fitting, chemical splash goggles or face shield.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and

before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat,

drink or smoke.

**Respiratory protection** If ventilation is inadequate, suitable respiratory protection must be worn.

## 9. Physical and chemical properties

# Information on basic physical and chemical properties

# **EPO-TEK® E4110 PMF Syringe**

Appearance Paste.

Color Silver.

Odor Mild.

Odor threshold
 PH
 No specific test data are available.
 Melting point
 No specific test data are available.

Initial boiling point and range No specific test data are available.

Flash point > 93°C
Evaporation rate < BuAc

Evaporation factor No specific test data are available.

Flammability (solid, gas) No specific test data are available.

Upper/lower flammability or No specific test data are available.

Vapor pressure No specific test data are available.

Vapor density > 1

explosive limits

Relative density

No specific test data are available.

Solubility(ies)

No specific test data are available.

Partition coefficient

No specific test data are available.

Auto-ignition temperature

No specific test data are available.

Decomposition Temperature

No specific test data are available.

Viscosity

No specific test data are available.

Other information None.

# 10. Stability and reactivity

**Reactivity** The following materials may react with the product: Strong acids. Strong alkalis.

Stability Stable at normal ambient temperatures.

Possibility of hazardous

reactions

May polymerize.

Conditions to avoid Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of

ignition. Avoid exposure to high temperatures or direct sunlight.

Materials to avoid Strong alkalis. Strong acids.

Hazardous decomposition

products

Thermal decomposition or combustion products may include the following substances:

Carbon monoxide (CO). Carbon dioxide (CO2).

# 11. Toxicological information

# Information on toxicological effects

Acute toxicity - oral

# **EPO-TEK® E4110 PMF Syringe**

**ATE oral (mg/kg)** 3,064.57

Acute toxicity - dermal

**ATE dermal (mg/kg)** 28,754.47

Acute toxicity - inhalation

ATE inhalation (gases ppm) 117,631.9

ATE inhalation (vapours mg/l) 287.54

ATE inhalation (dusts/mists

mg/l)

39.21

Inhalation Inhalation of dust during cutting, grinding or sanding operations involving this product may

cause irritation of the respiratory tract. Gas or vapor in high concentrations may irritate the

respiratory system.

**Ingestion** May cause discomfort if swallowed.

**Skin Contact** Causes severe burns. May cause sensitisation by skin contact.

**Eye contact** Causes burns. Causes serious eye damage.

12. Ecological information

**Ecotoxicity** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Acute aquatic toxicity

Acute toxicity - fish Not available.

Persistence and degradability

Persistence and degradability No data available.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient No specific test data are available.

Mobility in soil

Mobility No data available.

Other adverse effects

Other adverse effects Not known.

13. Disposal considerations

Waste treatment methods

**Disposal methods**Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

14. Transport information

**UN Number** 

**UN No. (TDG)** 2735

UN No. (IMDG) 2735

**UN No. (ICAO)** 2735

# **EPO-TEK® E4110 PMF Syringe**

**UN No. (DOT)** UN2735

UN proper shipping name

Proper shipping name (TDG) AMINES, LIQUID, CORROSIVE, N.O.S. (User to define)

Proper shipping name (IMDG) AMINES, LIQUID, CORROSIVE, N.O.S. (User to define)

Proper shipping name (ICAO) AMINES, LIQUID, CORROSIVE, N.O.S. (User to define)

Proper shipping name (DOT) AMINES, LIQUID, CORROSIVE, N.O.S. (User to define)

Transport hazard class(es)

DOT hazard class 8

DOT hazard label 8

TDG class 8

TDG label(s) 8

IMDG Class 8

ICAO class/division 8

# Transport labels



# **DOT transport labels**



# Packing group

TDG Packing Group III

IMDG packing group III

ICAO packing group

DOT packing group III

# **Environmental hazards**

# **Environmentally Hazardous Substance**



# Special precautions for user

IMDG Code segregation 18. Alkalis

group

**EmS** F-A, S-B

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

# **EPO-TEK® E4110 PMF Syringe**

# 15. Regulatory information

Regulatory References

Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of

Intellectual Property Rights (TRIPS), Section 7, Art. 39.

#### **US Federal Regulations**

## SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are required to be listed.

# CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed:

Silver

1,000 lbs (454 Kg)

## SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are required to be listed.

#### SARA 313 Emission Reporting

The following ingredients are listed:

Silver

#### **CAA Accidental Release Prevention**

None of the ingredients are required to be listed.

#### **OSHA Highly Hazardous Chemicals**

None of the ingredients are required to be listed.

# **US State Regulations**

# California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are required to be listed.

#### California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed:

Silver

#### California Air Toxics "Hot Spots" (A-II)

None of the ingredients are required to be listed.

# Massachusetts "Right To Know" List

The following ingredients are listed:

Silver

# Rhode Island "Right To Know" List

The following ingredients are listed:

Silver

#### Minnesota "Right To Know" List

The following ingredients are listed:

Silver

# New Jersey "Right To Know" List

The following ingredients are listed:

Silver

# **EPO-TEK® E4110 PMF Syringe**

# Pennsylvania "Right To Know" List

The following ingredients are listed:

Silver

#### **Inventories**

#### **EU - EINECS/ELINCS**

Some of the ingredients are listed or exempt.

#### Canada - DSL/NDSL

All the ingredients are listed or exempt.

#### **US-TSCA**

All the ingredients are listed or exempt.

#### US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

#### Australia - AICS

All the ingredients are listed or exempt.

#### Japan - ENCS

Some of the ingredients are listed or exempt.

#### Korea - KECI

All the ingredients are listed or exempt.

# China - IECSC

All the ingredients are listed or exempt.

#### Philippines - PICCS

All the ingredients are listed or exempt.

#### 16. Other information

Revision date 8/14/2019

Revision 1

Hazard statements in full H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.