



SAFETY DATA SHEET

EPO-TEK H20E-MP PMF Syringe

1. Identification

Product identifier

Product name EPO-TEK H20E-MP PMF Syringe

Product number H20E-MP

Recommended use of the chemical and restrictions on use

Application Adhesive.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.
14 Fortune Drive
Billerica, MA 01821
USA
(978) 667-3805
(978) 663-9782
www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

Label elements

Pictogram



Signal word

Danger

Hazard statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P264 Wash contaminated skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P302+P352 If on skin: Wash with plenty of water.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P501 Dispose of contents/ container in accordance with national regulations.

EPO-TEK H20E-MP PMF Syringe

Contains Silver, Epoxy Phenol Novolac, Reactive Diluent, Substituted Imidazole

Other hazards

Hazards not otherwise classified (HNOC) Contains epoxy constituents. May produce an allergic reaction.

3. Composition/information on ingredients

Mixtures

Silver	60-100%
CAS number: 7440-22-4	
Classification	
Aquatic Chronic 2 - H411	
Epoxy Phenol Novolac	10-30%
CAS number: 9003-36-5	
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
Reactive Diluent	1-5%
CAS number: Proprietary	
Classification	
Acute Tox. 4 - H302	
Eye Dam. 1 - H318	
STOT SE 3 - H336	
Substituted Imidazole	1-5%
CAS number: Proprietary	
Classification	
Acute Tox. 4 - H302	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
STOT SE 3 - H335	

The Full Text for all Hazard Statements are Displayed in Section 16.

4. First-aid measures

Description of first aid measures

Inhalation Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.

EPO-TEK H20E-MP PMF Syringe

Skin Contact Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

Most important symptoms and effects, both acute and delayed

Inhalation Gas or vapor in high concentrations may irritate the respiratory system. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.

Ingestion May cause discomfort if swallowed.

Skin contact Causes skin irritation. May cause sensitisation by skin contact.

Eye contact Causes serious eye damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Dry chemicals. Foam. Carbon dioxide (CO₂).

Special hazards arising from the substance or mixture

Hazardous combustion products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapors. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Avoid release to the environment. Do not discharge into drains or watercourses or onto the ground.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

Reference to other sections For personal protection, see Section 8.

7. Handling and storage

Precautions for safe handling

Usage precautions Handle all packages and containers carefully to minimize spills. Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet.

EPO-TEK H20E-MP PMF Syringe

Advice on general occupational hygiene

Provide eyewash station. Do not eat, drink or smoke when using this product. Wash promptly with soap and water if skin becomes contaminated. Wash after use and before eating, smoking and using the toilet. Wash contaminated clothing before reuse. Use appropriate skin cream to prevent drying of skin.

Conditions for safe storage, including any incompatibilities

Storage precautions Store at -40 degrees C. Keep container tightly sealed when not in use.

Storage class Chemical storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Silver

Long-term exposure limit (8-hour TWA): ACGIH 0.1 mg/m³

Short-term exposure limit (15-minute): ACGIH

ACGIH = American Conference of Governmental Industrial Hygienists.

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Liquid.
Color	Silver.
Odor	Mild.
Flash point	> 93°C
Evaporation rate	<BuAc
Other information	None.

EPO-TEK H20E-MP PMF Syringe

10. Stability and reactivity

Reactivity	The following materials may react violently with the product: Strong oxidizing agents.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	May polymerize.
Conditions to avoid	Avoid excessive heat for prolonged periods of time.
Materials to avoid	Strong oxidizing agents.
Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO ₂).

11. Toxicological information

Information on toxicological effects

Inhalation	Gas or vapor in high concentrations may irritate the respiratory system. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.
Ingestion	May cause discomfort if swallowed.
Skin Contact	May cause sensitisation by skin contact. Irritating to skin.
Eye contact	Causes serious eye damage.

12. Ecological Information

Ecotoxicity	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Toxicity	
Acute toxicity - fish	Not available.
Persistence and degradability	
Persistence and degradability	The product is biodegradable.
Bioaccumulative potential	
Bio-Accumulative Potential	The product contains potentially bioaccumulating substances.
Mobility in soil	
Mobility	Mobile.
Other adverse effects	
Other adverse effects	Not known.

13. Disposal considerations

Waste treatment methods

Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
-------------------------	---

EPO-TEK H20E-MP PMF Syringe

14. Transport information

UN Number

UN No. (TDG)	3082
UN No. (IMDG)	3082
UN No. (ICAO)	3082
UN No. (DOT)	UN3082

UN proper shipping name

Proper shipping name (TDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Silver, Epoxy Phenol Novolac)
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Silver, Epoxy Phenol Novolac)
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Silver, Epoxy Phenol Novolac)
Proper shipping name (DOT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Silver, Epoxy Phenol Novolac)

Transport hazard class(es)

DOT hazard class	9
DOT hazard label	9
TDG class	9
TDG label(s)	9
IMDG Class	9
ICAO class/division	9

Transport labels



DOT transport labels

Packing group

TDG Packing Group	III
IMDG packing group	III
ICAO packing group	III
DOT packing group	III

Environmental hazards

EPO-TEK H20E-MP PMF Syringe

Environmentally Hazardous Substance



Special precautions for user

EmS F-A, S-F

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Regulatory References Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of Intellectual Property Rights (TRIPS), Section 7, Art. 39.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are required to be listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed:

Silver

1,000 lbs (454 Kg)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are required to be listed.

SARA 313 Emission Reporting

The following ingredients are listed:

Silver

CAA Accidental Release Prevention

None of the ingredients are required to be listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are required to be listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are required to be listed.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed:

Silver

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are required to be listed.

Massachusetts "Right To Know" List

The following ingredients are listed:

Silver

EPO-TEK H20E-MP PMF Syringe

Rhode Island "Right To Know" List

The following ingredients are listed:

Silver

Minnesota "Right To Know" List

The following ingredients are listed:

Silver

New Jersey "Right To Know" List

The following ingredients are listed:

Silver

Pennsylvania "Right To Know" List

The following ingredients are listed:

Silver

Inventories

EU - EINECS/ELINCS

Some of the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed.

Australia - AICS

All the ingredients are listed or exempt.

Japan - MITI

Some of the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

All the ingredients are listed or exempt.

16. Other information

Revision date 7/26/2016

Revision 1

EPO-TEK H20E-MP PMF Syringe

Hazard statements in full

H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.