

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : EPO-TEK® OG142-87 PMF SYRINGE

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : adhesives  
Recommended use : adhesives  
Restrictions on use : Not to be used for any purpose other than the one the product was designed for

#### 1.3. Supplier

Epoxy Technology, Inc.  
14 Fortune Drive  
Billerica, MA 01821, 01821  
USA  
T 978-667-3805 - F 978-663-9782  
[www.epotek.com](http://www.epotek.com)

#### 1.4. Emergency telephone number

Emergency number : ChemTel: +1 (800) 255-3924, +1 (813) 248-0585

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Hazardous to the aquatic environment – Acute Hazard Category 3	H402	Harmful to aquatic life
Hazardous to the aquatic environment – Chronic Hazard Category 3	H412	Harmful to aquatic life with long lasting effects

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning  
Hazard statements (GHS US) : H317 - May cause an allergic skin reaction  
H402 - Harmful to aquatic life  
H412 - Harmful to aquatic life with long lasting effects  
Precautionary statements (GHS US) : P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 - If on skin: Wash with plenty of water.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P363 - Wash contaminated clothing before reuse.

# EPO-TEK® OG142-87 PMF SYRINGE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Epoxy resin*	CAS-No.: Trade Secret	≥ 60	Skin Sens. 1, H317 Aquatic Chronic 3, H412
Photoinitiator*	CAS-No.: Trade Secret	< 1	Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Photoinitiator*	CAS-No.: Trade Secret	< 1	Eye Irrit. 2, H319 Skin Sens. 1, H317

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Comments : Components not listed are either non-hazardous or are below reportable limits.

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : May cause an allergic skin reaction.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

# EPO-TEK® OG142-87 PMF SYRINGE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.  
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### EPO-TEK® OG142-87 PMF SYRINGE

No additional information available

# EPO-TEK® OG142-87 PMF SYRINGE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Epoxy resin

No additional information available

### Photoinitiator

No additional information available

### Photoinitiator

No additional information available

## 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

## 8.3. Individual protection measures/Personal protective equipment

### Hand protection:

Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear

### Eye protection:

Safety glasses

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: clear
Odor	: Mild odor
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available

# EPO-TEK® OG142-87 PMF SYRINGE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Epoxy resin	
LD50 oral rat	4490 mg/kg (Rat, Oral)
LD50 dermal rat	> 2000 mg/kg (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)
LC50 Inhalation - Rat	> 20 mg/l (4 h, Rat, Inhalation)
ATE US (oral)	4490 mg/kg body weight

# EPO-TEK® OG142-87 PMF SYRINGE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Photoinitiator	
LD50 oral rat	> 5110 mg/kg body weight (EU Method B.1: Acute Toxicity (Oral), Rat, Male / female, Experimental value, Oral)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: May cause an allergic skin reaction.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Epoxy resin	
LC50 - Fish [1]	24 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	40 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)

Photoinitiator	
EC50 - Crustacea [1]	0.8 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia sp., Experimental value)
ErC50 algae	0.184 mg/l (EU Method C.3, 72 h, Selenastrum capricornutum, Experimental value, GLP)

Photoinitiator	
EC50 - Crustacea [1]	0.148 mg/l

### 12.2. Persistence and degradability

Epoxy resin	
Persistence and degradability	Biodegradability in soil: no data available. Readily biodegradable in water.
ThOD	2.16 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

Epoxy resin	
Partition coefficient n-octanol/water (Log Pow)	1.34 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Photoinitiator	
Partition coefficient n-octanol/water (Log Pow)	1 (Practical experience/observation, EU Method A.8: Partition Coefficient, 20 °C)

# EPO-TEK® OG142-87 PMF SYRINGE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Photoinitiator	
Partition coefficient n-octanol/water (Log Pow)	27.109 Source: lookchem

### 12.4. Mobility in soil

Epoxy resin	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.4195 (log Koc, QSAR)
Ecology - soil	Low potential for adsorption in soil. Highly mobile in soil.

Photoinitiator	
Surface tension	55.9 mN/m (20 °C, 18 mg/l, EU Method A.5: Surface tension)

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

### 14.1. UN number

Not regulated for transport

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable  
Proper Shipping Name (TDG) : Not applicable  
Proper Shipping Name (IMDG) : Not applicable  
Proper Shipping Name (IATA) : Not applicable

### 14.3. Transport hazard class(es)

**DOT**  
Transport hazard class(es) (DOT) : Not applicable

**TDG**  
Transport hazard class(es) (TDG) : Not applicable

**IMDG**  
Transport hazard class(es) (IMDG) : Not applicable

**IATA**  
Transport hazard class(es) (IATA) : Not applicable

### 14.4. Packing group

Packing group (DOT) : Not applicable  
Packing group (TDG) : Not applicable

# EPO-TEK® OG142-87 PMF SYRINGE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### DOT

No data available

#### TDG

No data available

#### IMDG

No data available

#### IATA

No data available

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### 15.2. International regulations

#### CANADA

##### Epoxy resin

Listed on the Canadian DSL (Domestic Substances List)

##### Photoinitiator

Listed on the Canadian NDSL (Non-Domestic Substances List)

##### Photoinitiator

Listed on the Canadian NDSL (Non-Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

No additional information available

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm



# EPO-TEK® OG142-87 PMF SYRINGE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.