

SAFETY DATA SHEET EPO-TEK TJ2139-LH PMF Syringe

1. Identification

Product identifier

Product name EPO-TEK TJ2139-LH PMF Syringe

Product number TJ2139-LH

Recommended use of the chemical and restrictions on use

Application Adhesive.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.

14 Fortune Drive Billerica, MA 01821

USA

(978) 667-3805 (978) 663-9782 www.epotek.com

Emergency telephone number

Emergency telephone +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

Label elements

Pictogram







Signal word

Danger

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P501 Dispose of contents/container in accordance with national regulations.

EPO-TEK TJ2139-LH PMF Syringe

Contains Epoxy Phenol Novolac

Other hazards

Harmful dust may be released during cutting or grinding process.

3. Composition/information on ingredients

Mixtures

CAS number: 9003-36-5

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

Substituted Imidazole 1-5%

CAS number: Proprietary

Classification

Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Acute Tox. 4 - H302 STOT SE 3 - H335

The Full Text for all Hazard Statements are Displayed in Section 16.

4. First-aid measures

Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Maintain

an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place. Never give anything by mouth to an unconscious person. Get medical attention if any

discomfort continues.

Ingestion Remove affected person from source of contamination. Rinse nose and mouth with water.

Give plenty of water to drink. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. Do not induce vomiting unless under the direction of medical personnel. Place unconscious person on their side in the recovery position and ensure breathing can take place. Never give anything by mouth to an unconscious person. Get medical attention if any

discomfort continues.

Skin Contact Remove contaminated clothing and rinse skin thoroughly with water. Continue to rinse for at

least 10 minutes. Do not use organic solvents. Get medical attention if irritation persists after

washing.

Eye contact Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do.

Continue rinsing. Continue to rinse for at least 15 minutes and get medical attention.

Most important symptoms and effects, both acute and delayed

EPO-TEK TJ2139-LH PMF Syringe

Inhalation Inhalation of dust during cutting, grinding or sanding operations involving this product may

cause irritation of the respiratory tract. Gas or vapor in high concentrations may irritate the

respiratory system.

Ingestion May cause discomfort if swallowed.

Skin contact Causes skin irritation. May cause sensitisation by skin contact.

Eye contact Causes serious eye damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

5.Fire-fighting measures

Extinguishing media

Suitable extinguishing media Dry chemicals. Foam. Carbon dioxide (CO2).

Special hazards arising from the substance or mixture

Hazardous combustion

Thermal decomposition or combustion products may include the following substances:

Carbon monoxide (CO). Carbon dioxide (CO2).

Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapors. Use water to keep fire exposed containers cool and

disperse vapors.

Special protective equipment

for firefighters

products

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Avoid discharge to the aquatic environment.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if safe to do so. Eliminate all sources of ignition. Absorb in vermiculite, dry sand or

earth and place into containers. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Dispose of

contents/container in accordance with national regulations.

Reference to other sections For personal protection, see Section 8.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Wear protective clothing as described in

Section 8 of this safety data sheet.

Advice on general occupational hygiene

Provide eyewash station. Do not eat, drink or smoke when using this product. Wash promptly if skin becomes contaminated. Wash after use and before eating, smoking and using the

toilet. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions Store at -40 degrees C. Keep container tightly sealed when not in use.

EPO-TEK TJ2139-LH PMF Syringe

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate general and local exhaust ventilation.

Eye/face protection Wear tight-fitting, chemical splash goggles or face shield.

Hand protection It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures Provide eyewash station. Do not eat, drink or smoke when using this product. Wash promptly

if skin becomes contaminated. Wash after use and before eating, smoking and using the

toilet. Wash contaminated clothing before reuse.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

AppearancePaste.ColorCream.OdorMild.Flash point> 93°CVapour density> Air

Other information None.

10. Stability and reactivity

Reactivity The following materials may react with the product: Strong reducing agents. Strong oxidizing

agents.

Stability Stable at normal ambient temperatures and when used as recommended.

Possibility of hazardous

reactions

Will not polymerize.

Conditions to avoid Avoid excessive heat for prolonged periods of time.

Materials to avoid Strong reducing agents. Strong oxidizing agents.

Hazardous decomposition

products

Thermal decomposition or combustion products may include the following substances:

Carbon monoxide (CO). Carbon dioxide (CO2).

EPO-TEK TJ2139-LH PMF Syringe

11. Toxicological information

Information on toxicological effects

Inhalation Inhalation of dust during cutting, grinding or sanding operations involving this product may

cause irritation of the respiratory tract. Gas or vapor in high concentrations may irritate the

respiratory system.

Ingestion May cause discomfort if swallowed.

Skin Contact Causes skin irritation. May cause sensitisation by skin contact.

Eye contact Causes serious eye damage.

12. Ecological Information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Toxicity

Acute toxicity - fish Not available.

Persistance and degradability

Persistence and degradability No data available.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Mobility in soil

Mobility No data available.

Other adverse effects

Other adverse effects Not known.

13. Disposal considerations

Waste treatment methods

Disposal methodsDispose of contents/container in accordance with national regulations. Dispose of waste to

licensed waste disposal site in accordance with the requirements of the local Waste Disposal

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy

Authority.

14. Transport information

UN Number

UN No. (DOT) 3082 UN No. (IMDG) 3082 UN No. (ICAO) 3082

UN proper shipping name

Proper shipping name (DOT) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy

Phenol Novolac)

Proper shipping name

(IMDG) Phenol Novolac)

Phonol Novolac)

EPO-TEK TJ2139-LH PMF Syringe

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Phenol Novolac)

Transport hazard class(es)

IMDG Class 9
ICAO class/division 9

Transport labels



Packing group

DOT pack group III
IMDG packing group III
ICAO packing group III

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

EmS F-A, S-F

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are required to be listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are required to be listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are required to be listed.

SARA 313 Emission Reporting

None of the ingredients are required to be listed.

CAA Accidental Release Prevention

None of the ingredients are required to be listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are required to be listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are required to be listed.

EPO-TEK TJ2139-LH PMF Syringe

California Air Toxics "Hot Spots" (A-I)

None of the ingredients are required to be listed.

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are required to be listed.

Massachusetts "Right To Know" List

None of the ingredients are required to be listed.

Rhode Island "Right To Know" List

None of the ingredients are required to be listed.

Minnesota "Right To Know" List

None of the ingredients are required to be listed.

New Jersey "Right To Know" List

None of the ingredients are required to be listed.

Pennsylvania "Right To Know" List

None of the ingredients are required to be listed.

Inventories

EU - EINECS/ELINCS

Some of the ingredients are listed or exempt.

Canada - DSL/NDSL

Some of the ingredients are listed or exempt.

US-TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

Australia - AICS

Some of the ingredients are listed or exempt.

Japan - MITI

Some of the ingredients are listed or exempt.

Korea - KECI

Some of the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

All the ingredients are listed or exempt.

16. Other information

Revision date 8/24/2015

Revision 1

EPO-TEK TJ2139-LH PMF Syringe

Hazard statements in full H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.